




ROBO-FIT, LLC









TRANSPORTATION PRODUCT CATALOG






Connecting Like Family












440-893-9878

WWW.ROBO-FIT.COM

Male Pipe Size	
	1/8"-27 NPTF
	1/4"-18 NPTF
	3/8"-18 NPTF
	1/2"-14 NPTF
	3/4"-14 NPTF
	1"-11.5 NPTF

SCALE- 1:1



Hex Size	
	
	
	
	
	
	
	

**TABLE OF CONTENTS**

CATALOG SECTION	PAGE NUMBER
BRASS PIPE FITTINGS	2-9
STEEL BULKHEADS & ADAPTERS	10-13
BRASS HOSE BARB FITTINGS	14-20
BRASS PUSH-LOK HOSE BARB FITTINGS	21-25
BRASS FLARE FITTINGS	26-36
NYLON AIR BRAKE DOT FITTINGS	37-41
BRASS PUSH-IN DOT FITTINGS	42-48
COMPOSITE PUSH-IN DOT FITTINGS	49-53
NYLON AIR BRAKE TUBING	54-55
AIR BRAKE HOSE ENDS	56-59
J1402 AIR BRAKE HOSE	60
DRAIN & TRUCK VALVES	61-63
SELECTOR VALVES	64-66
PANEL MOUNT BALL VALVES	67-68
INDUSTRIAL BALL VALVES	69-70
CHECK VALVES	71-72
BRASS MINI BALL VALVES	73-74
PUSH BUTTON VALVES	75
PRODUCT WARRANTY	76
PRODUCT INDEX	77
PIPE THREAD SPECIFICATIONS	78
FITTING CONFIGURATION AND NUMBERING	79-80
PROPOSITION 65	81
SAE SPECIFICATIONS	82
FITTING ASSEMBLY REFERENCE CHART	83
QUALITY CONTROL EQUIPMENT	84



BRASS PIPE FITTINGS

CONSTRUCTION	• CA360, CA345, CA3604, CA377 Brass
APPLICATIONS	• Use with brass, copper or iron pipe
RANGES	• Temperature Range: 65° to +250° F. • Pressure Range: Up to 1000 PSI



Pipe Thread Assembly:

Straight Fittings:

1. Hand Tighten
2. 1/8" to 1/2": Wrench Tight 2 Full 360° Turns
1/2" & Above: 1 1/2" Full Turns


Shaped Fittings:

1. Hand Tighten
2. Wrench Tight 1" to 1 1/2" Full 360° Turns

**For NPTF Pipe Threads with Pre-Applied Sealant*


ORDERING INFORMATION

- Parts that include "F" in the part number, for example, 101AF-A, are supplied forgings.
- Parts that include "PBF" or "LF" are supplied as low lead compliant fittings.
- Part number without the "PBF" distinction are NOT lead free compliant.
- Nomenclature Example:



NOTES

- Non-stock items and special parts are available on a quotation basis.
- Configurations and dimensions are subject to change without notice.








Quality Matters!

Our Pipe Threads are made with the proper wall thickness and are made to dry-seal specifications.




WARNING: Products offered by Robo-Fit can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov

100A 90° Female Elbow 	100-45A 45° Female Elbow 	101A Female Pipe Tee 	102A Female Cross Tee 	103A Female Coupling 	104A Ground Joint 
108A Pipe Cap 	109A (Cored) Square Head Plug 	109AS (Solid) Square Head Plug 	109CS Counter Sunk Plug 	110FB Face Bushing 	110A Hex Bushing 
111A Lock Nut 	112A Close Nipple 	113A Yellow Brass Nipple 	113RB Red Brass Nipple 	116A 90° Street Elbow 	116AL 90° Long Street Elbow 
116AM 90° Male Elbow 	117A Slotted Plug 	119A Reducer 	120A Adapter 	121A (Cored) Hex Head Plug 	121AS (Solid) Hex Head Plug 
122A Hex Nipple 	123A Hex Reducing Nipple 	124A 45° Street Elbow 	127A Street Tee 	127S Street Tee (FXMXM) 	T9 Branch Tee 
129A Bulkhead 					

100A 90° ELBOW FPT TO FPT

PART NUMBER	PIPE THREAD	A	B
100A-A	1/8"	.59	.59
100AF-A	1/8"	.58	.58
100A-B	1/4"	.78	.78
100AF-B	1/4"	.72	.72
100A-BA	1/4" x 1/8"	.72	.72
100A-C	3/8"	.84	.84
100A-CB	3/8" x 1/4"	.84	.84
100AF-CB	3/8" x 1/4"	.81	.81
100A-D	1/2"	.84	.84
100AF-D	1/2"	1.00	1.00
100A-DC	1/2" x 3/8"	1.00	1.00
100AF-DC	1/2" x 3/8"	1.00	1.00
100A-E	3/4"	1.18	1.18
100AF-E	3/4"	1.10	1.10

REF SAE 130238



Forged Style





Barstock Style

101A TEE FPT ALL ENDS

PART NUMBER	PIPE THREAD	A	B
101A-A	1/8"	.56	.56
101AF-A	1/8"	.56	.56
101A-B	1/4"	.75	.75
101AF-B	1/4"	.72	.72
101A-BBA	1/4" x 1/4" x 1/8"	.69	.69
101A-C	3/8"	.84	.84
101AF-C	3/8"	.84	.84
101A-CCB	3/8" x 3/8" x 1/4"	.80	.85
101A-D	1/2"	1.09	1.09
101AF-D	1/2"	.98	.98
100A-DDC	1/2" x 1/2" x 3/8"	1.00	1.00
101A-E	3/4"	1.18	1.18
101AF-E	3/4"	1.13	1.13

REF SAE 130438




Forged Style



Barstock Style

100-45A ELBOW 45° FPT TO FPT


PART NUMBER	PIPE THREAD	A	B
100-45A-A	1/8"	.46	.46
100-45A-B	1/4"	.64	.64
100-45A-C	3/8"	.61	.61
100-45A-D	1/2"	.91	.91
100-45A-E	3/4"	1.00	1.00



Barstock Style

102A CROSS FPT ALL ENDS

PART NUMBER	PIPE THREAD	A
102A-A	1/8"	.65
102AF-A	1/8"	.52
102A-B	1/4"	.78
102AF-B	1/4"	.66
102A-C	3/8"	.98
102AF-C	3/8"	.82
102AF-D	1/2"	1.08
102A-D	1/2"	1.07
102AF-E	3/4"	1.18



Forged Style




Barstock Style

103A COUPLING FPT TO FPT


PART NUMBER	PIPE THREAD	A	HEX
103AH-A	1/8"	.75	9/16"
103AH-B	1/4"	1.12	3/4"
103AH-C	3/8"	1.12	7/8"
103AH-D	1/2"	1.50	1-1/16"
103AH-E	3/4"	1.53	1-3/8"

REF SAE 130138




109A SQUARE HEAD PLUG CORED

PART NUMBER	PIPE THREAD	A
109A-A	1/8"	.58
109A-B	1/4"	.70
109A-C	3/8"	.73
109A-D	1/2"	.93
109A-E	3/4"	1.00
109A-F	1"	1.20



104A GROUND JOINT UNION FPT TO FPT

PART NUMBER	PIPE THREAD	A	HEX
104A-A	1/8"	1.19	9/16"
104A-B	1/4"	1.22	11/16"
104A-C	3/8"	1.72	11/16"
104A-D	1/2"	1.78	15/16"
104A-E	3/4"	1.88	1-1/4"




109AS SQUARE HEAD PLUG SOLID

PART NUMBER	PIPE THREAD	A
109AS-D	1/2"	.93
109AS-E	3/4"	1.00
109AS-F	1"	1.20




109CS COUNTER-SUNK PLUG

PART NUMBER	PIPE THREAD	A
109CS-A	1/8"	.30
109CS-B	1/4"	.45
109CS-C	3/8"	.45
109CS-D	1/2"	.60
109CS-E	3/4"	.55




108A PIPE CAP

PART NUMBER	PIPE THREAD	A	HEX
108A-A	1/8"	.47	9/16"
108A-B	1/4"	.59	11/16"
108A-C	3/8"	.69	13/16"
108A-D	1/2"	.78	15/16"
108A-E	3/4"	.94	1-1/4"




110FB FACE BUSHING

PART NUMBER	PIPE THREAD	A
110FB-CB	3/8" x 1/4"	.50
110FB-DB	1/2" x 1/4"	.53
110FB-DC	1/2" x 3/8"	.53
110FB-ED	3/4" x 1/2"	.55



110A HEX BUSHING


PART NUMBER	PIPE THREAD	A	HEX
110A-BA	1/4" x 1/8"	.62	9/16"
110AH-BA	1/4" x 1/8"	.75	9/16"
110A-CA	3/8" x 1/8"	.69	11/16"
110AH-CA	3/8" x 1/8"	.75	11/16"
110A-CB	3/8" x 1/4"	.69	11/16"
110AH-CB	3/8" x 1/4"	.75	3/4"
110A-DA	1/2" x 1/8"	.81	13/16"
110AH-DA	1/2" x 1/8"	1.00	7/8"
110A-DB	1/2" x 1/4"	.81	13/16"
110AH-DB	1/2" x 1/4"	1.00	7/8"
110A-DC	1/2" x 3/8"	.81	13/16"
110AH-DC	1/2" x 3/8"	1.00	7/8"
110A-EA	3/4" x 1/8"	.94	1-1/16"
110AH-EA	3/4" x 1/8"	1.00	1-1/8"
110A-EB	3/4" x 1/4"	.94	1-1/16"
110AH-EB	3/4" x 1/4"	1.00	1-1/8"
110A-EC	3/4" x 3/8"	.94	1-1/16"
110AH-EC	3/4" x 3/8"	1.00	1-1/8"
110A-ED	3/4" x 1/2"	.94	1-1/16"
110AH-ED	3/4" x 1/2"	1.00	1-1/8"
110A-FB	1" x 1/4"	1.12	1-3/8"
110A-FC	1" x 3/8"	1.12	1-3/8"
110A-FD	1" x 1/2"	1.12	1-3/8"
110A-FE	1" x 3/4"	1.12	1-3/8"



REF SAE 130140 (AH Style)


111A LOCK NUT

PART NUMBER	PIPE THREAD	A	HEX
111A-A	1/8"	.19	11/16"
111A-B	1/4"	.25	7/8"
111A-C	3/8"	.31	1"
111A-D	1/2"	.25	1-1/8"
111A-E	3/4"	.33	1-1/2"




112A CLOSE NIPPLE

PART NUMBER	PIPE THREAD	A
112A-A	1/8"	.75
112A-B	1/4"	.88
112A-C	3/8"	1.00
112A-D	1/2"	1.12
112A-E	3/4"	1.31
112A-F	1"	1.31




113A LONG NIPPLE (YELLOW BRASS)

PART NUMBER	PIPE THREAD	A
113A-A15	1/8"	1-1/2"
113A-B15	1/4"	1-1/2"
113A-C15	3/8"	1-1/2"
113A-D15	1/2"	1-1/2"
113A-E15	3/4"	1-1/2"
113A-A2	1/8"	2"
113A-B2	1/4"	2"
113A-C2	3/8"	2"
113A-D2	1/2"	2"
113A-A25	1/8"	2.5"
113A-B25	1/4"	2.5"
113A-C25	3/8"	2.5"
113A-D25	1/2"	2.5"
113A-E25	3/4"	2.5"
113A-E3	3/4"	2"





113RB LONG NIPPLE (RED BRASS)

PART NUMBER	PIPE THREAD	A
113RB-A25	1/8"	2-1/2"
113RB-B25	1/4"	2-1/2"
113RB-C25	3/8"	2-1/2"
113RB-D25	1/2"	2-1/2"
113RB-E25	3/4"	2-1/2"
113RB-A3	1/8"	3"
113RB-B3	1/4"	3"
113RB-C3	3/8"	3"
113RB-D3	1/2"	3"
113RB-E3	3/4"	3"
113RB-A35	1/8"	3-1/2"
113RB-B35	1/4"	3-1/2"
113RB-C35	3/8"	3-1/2"
113RB-D35	1/2"	3-1/2"
113RB-E35	3/4"	3-1/2"
113RB-A4	1/8"	4"
113RB-B4	1/4"	4"
113RB-C4	3/8"	4"
113RB-D4	1/2"	4"
113RB-E4	3/4"	4"
113RB-A45	1/8"	4-1/2"
113RB-B45	1/4"	4-1/2"
113RB-C45	3/8"	4-1/2"
113RB-D45	1/2"	4-1/2"
113RB-E45	3/4"	4-1/2"
113RB-A5	1/8"	5"
113RB-B5	1/4"	5"
113RB-C5	3/8"	5"
113RB-D5	1/2"	5"
113RB-E5	3/4"	5"
113RB-A55	1/8"	5-1/2"
113RB-B55	1/4"	5-1/2"
113RB-C55	3/8"	5-1/2"
113RB-D55	1/2"	5-1/2"
113RB-E55	3/4"	5-1/2"
113RB-A6	1/8"	6"
113RB-B6	1/4"	6"
113RB-C6	3/8"	6"
113RB-D6	1/2"	6"
113RB-E6	3/4"	6"




116A 90° STREET ELBOW


PART NUMBER	PIPE THREAD	A	B
116A-A	1/8"	.62	.35
116AF-A	1/8"	.81	.56
116A-A-BK	1/8"	.62	.48
116A-B	1/4"	.78	.43
116AF-B	1/4"	.86	.44
116A-B-BK	1/4"	.91	.72
116A-C	3/8"	1.00	.89
116AF-C	3/8"	.98	.68
116A-C-BK	3/8"	.97	.78
116A-D	1/2"	1.25	1.03
116AF-D	1/2"	1.43	.94
116A-D-BK	1/2"	1.25	1.03
116A-E	3/4"	1.40	1.08
116AF-E	3/4"	1.50	.91
116A-E-BK	3/4"	1.39	1.10



Mailbox Style




Forged Style



Block Style


116AL STREET ELBOW LONG PATTERN

PART NUMBER	PIPE THREAD	A	B
116AL-A	1/8"	.80	.46
116AL-B	1/4"	1.10	.68
116AL-C	3/8"	1.29	.95





116AM MALE ELBOW

PART NUMBER	PIPE THREAD	A	B
116AM-A	1/8"	.69	.69
116AMF-A	1/8"	.71	.71
116AM-B	1/4"	.88	.88
116AMF-B	1/4"	1.09	1.09
116AMF-BA	1/4" x 1/8"	.77	.95
116AM-C	3/8"	1.06	1.06
116AM-CB	3/8" x 1/4"	.92	.92
116AM-D	1/2"	1.40	1.40
116AMF-D	1/2"	1.41	1.41
116AM-DC	1/2" x 3/8"	1.02	1.12



120A ADAPTER FPT TO MPT


PART NUMBER	PIPE THREAD	A	Hex
120AH-AA	1/8" x 1/8"	.87	9/16"
120AH-BA	1/4" x 1/8"	1.06	3/4"
120AH-BB	1/4" x 1/4"	1.06	3/4"
120A-CA	3/8" x 1/8"	1.00	3/4"
120AH-CB	3/8" x 1/4"	1.25	7/8"
120AH-CC	3/8" x 3/8"	1.25	1.06
120AH-DB	1/2" x 1/4"	1.46	1-1/16"
120AH-DC	1/2" x 3/8"	1.46	1-1/16"
120AH-DD	1/2" x 1/2"	1.65	1-1/16"
120A-ED	3/4" x 1/2"	1.22	1-1/4"



REF SAE 130139 (AH Style)



117A SLOTTED PLUG

PART NUMBER	PIPE THREAD	A
117A-A	1/8"	.30
117A-B	1/4"	.45
117A-C	3/8"	.45





121A HEX HEAD PLUG CORED

PART NUMBER	PIPE THREAD	A	Hex
121A-A	1/8"	.56	7/16"
121A-B	1/4"	.62	9/16"
121A-C	3/8"	.72	11/16"
121A-D	1/2"	.81	7/8"
121A-E	3/4"	.84	1-1/16"
121A-F	1"	1.12	1-3/16"





119A REDUCER FPT TO FPT

PART NUMBER	PIPE THREAD	A	Hex
119AH-BA	1/4" x 1/8"	.96	3/4"
119A-CA	3/8" x 1/8"	1.00	3/4"
119AH-CB	3/8" x 1/4"	1.16	7/8"
119A-DA	1/2" x 1/8"	1.19	15/16"
119AH-DB	1/2" x 1/4"	1.38	1-1/16"
119AH-DC	1/2" x 3/8"	1.38	1-1/16"
119A-ED	3/4" x 1/2"	1.19	1-1/4"
119AH-ED	3/4" x 1/2"	1.50	1-3/8"



121AS HEX HEAD PLUG SOLID

PART NUMBER	PIPE THREAD	A	Hex
121AS-A	1/8"	.56	7/16"
121AS-B	1/4"	.62	9/16"
121AS-C	3/8"	.72	11/16"
121AS-D	1/2"	.81	7/8"
121AS-E	3/4"	.94	1-1/16"




REF SAE 130138 (AH Style)

122A HEX NIPPLE

PART NUMBER	PIPE THREAD	A	Hex
122AH-A	1/8"	.97	7/16"
122AH-B	1/4"	1.37	9/16"
122AH-C	3/8"	1.40	11/16"
122AH-D	1/2"	1.81	7/8"
122AH-E	3/4"	1.96	1-1/8"


REF SAE 130137



123A HEX REDUCING NIPPLE

PART NUMBER	PIPE THREAD	A	Hex
123AH-BA	1/4" x 1/8"	1.18	9/16"
123AH-CA	3/8" x 1/8"	1.21	11/16"
123AH-CB	3/8" x 1/4"	1.40	11/16"
123AH-DB	1/2" x 1/4"	1.62	7/8"
123AH-DC	1/2" x 3/8"	1.62	7/8"
123A-ED	3/4" x 1/2"	1.50	1-1/16"


REF SAE 130137 (AH Style)



124A STREET ELBOW 45°

PART NUMBER	PIPE THREAD	A	B
124A-A	1/8"	.38	.50
124A-B	1/4"	.74	.55
124A-C	3/8"	.78	.56
124A-D	1/2"	.98	.74
124A-E	3/4"	1.125	.75



REF SAE 130339



127A STREET TEE FPT TO MPT TO FPT

PART NUMBER	PIPE THREAD	A	B
127A-A	1/8"	.55	.56
127A-B	1/4"	.78	.91
127A-C	3/8"	.84	1.03
127A-D	1/2"	1.16	1.16



REF SAE 130339



T9 BRANCH TEE FPT TO FPT TO MPT



PART NUMBER	PIPE THREAD	A	B
T9-222	1/8"	.62	.31
T9-444	1/4"	1.50	.75
T9-666	3/8"	1.60	.80
T9-888	1/2"	2.14	1.07

REF SAE 130425



129A BULKHEAD ADAPTER

PART NUMBER	A	B	C
129A-A	1.50	1/8" FPT	5/8-18
129AS-B	.92	1/4" FPT	3/4-16
129A-B	1.50	1/4" FPT	3/4-16
129A-C	1.32	3/8" FPT	1-14
129A-D	1.50	1/2" FPT	1 1/8-14
129A-E	1.50	3/4" FPT	1-5/16-12





STEEL BULKHEADS & ADAPTERS

CONSTRUCTION	• AISI 1045 Steel, Carbon Steel:12L14 - Plating: ASTM B 633 Type V (High Corrosion Clear Trivalent)
APPLICATIONS	•Panel Mounts •Transportation: Air brake systems, trucks, trails, RVs.
RANGES	•Temperature Range: 0°F to 350° F. • Pressure Range: Up to 2500PSI



Pipe Thread Assembly:

Straight Fittings:

- 1. Hand Tighten
- 2. 1/8" to 1/2": Wrench Tight 2 Full 360° Turns
- 1/2" & Above: 1 1/2" Full Turns



Shaped Fittings:

- 1. Hand Tighten
- 2. Wrench Tight 1" to 1 1/2" Full 360° Turns



ORDERING INFORMATION

• Nomenclature Example:



Quality Matters!

Our pipe threads are made with the proper wall thickness and are made to dry-seal specifications.

NOTES

- Non-stock items and special parts are available on a quotation basis.
- Configurations and dimensions are subject to change without notice.

⚠ WARNING: Products offered by Robo-Fit can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov

RF21204

1/4" FPT (Short) Bulkhead Coupling




RF5465

1/4" FPT Bulkhead Coupling



RF5498

Steel Bulkhead Adapter Coupling



RF5730

Steel Bulkhead Adapter Coupling




RF17709

3/8" FPT Bulkhead Coupling




RF11304

Steel Bulkhead Adapter Coupling





5404

Steel Hex Nipple




RF21204 1/4" FPT Steel Bulkhead Coupling (Short)

PART NUMBER	FPT	FPT	STRAIGHT THREAD	A	BODY HEX	NUT HEX
RF21204	1/4"	1/4"	3/4"-16 UNF	.94"	1"	1.063"





RF5465 1/4" FPT Steel Bulkhead Coupling

PART NUMBER	FPT	FPT	STRAIGHT THREAD	A	BODY HEX	NUT HEX
RF5465	1/4"	1/4"	3/4"-16 UNF	1.25"	1"	1.063"





RF5498 Steel Bulkhead Adapter Coupling

PART NUMBER	MPT	FPT	STRAIGHT THREAD	A	BODY HEX	NUT HEX
RF5498	1/2"	1/4"	3/4"-16 UNF	2.16"	1.25"	1.063"




RF5730 Steel Bulkhead Adapter Coupling

PART NUMBER	MPT	FPT	STRAIGHT THREAD	A	BODY HEX	NUT HEX
RF5730	1/2"	1/4"	1"-14 UNS	2.94"	1.25"	1.375"





RF17709 3/8" Steel Bulkhead Coupling

PART NUMBER	FPT	FPT	STRAIGHT THREAD	A	BODY HEX	NUT HEX
RF17709	3/8"	3/8"	1"-14 UNS	1.31"	1.125"	1.25"





RF11304 Steel Bulkhead Adapter Coupling

PART NUMBER	MPT	FPT	STRAIGHT THREAD	A	BODY HEX	NUT HEX
RF11304	1/2"	3/8"	1"-14 UNS	2.15"	1.25"	1.25"



5404 Steel Hex Nipple


PART NUMBER	MPT	MPT	A	BODY HEX
5404-12-08	3/4"	1/2"	1.925"	1.125"
5404-12-12	3/4"	3/4"	1.96"	1.125"





BRASS HOSE BARB FITTINGS

CONSTRUCTION	• CA360/CA3604 Brass (Straights) • CA360/CA3604/CA377 Brass (Shapes)
APPLICATIONS	• Use with thermoplastic or rubber hose and tubing. For use with a hose clamp or crimped type fitting. • Temperature Range: -40° to 160° F.
RANGES	• Pressure Range: Up to 150 PSI



Pipe Thread Assembly:

Straight Fittings:

1. Hand Tighten
2. 1/8" to 1/2": Wrench Tight 2 Full 360° Turns
1/2" & Above: 1 1/2" Full Turns


Shaped Fittings:

1. Hand Tighten
2. Wrench Tight 1" to 1 1/2" Full 360° Turns

**For NPTF Pipe Threads with Pre-Applied Sealant*

ORDERING INFORMATION

- Parts that include "PBF" are supplied as low lead compliant fittings.
- Part numbers without the "PBF" distinction are NOT lead free compliant.
- Nomenclature Example:



NOTES

- Non-stock items and special parts are available on a quotation basis.
- Configurations and dimensions are subject to change without notice.

TYPES OF BARBS

Multi-Barb





Beaded Hose Barb




Beaded Barbs are popular with 1/2" Hose Sizes and above.

⚠ WARNING: Products offered by Robo-Fit can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov

201A Hose Barb to MPT 	201A-SV Hose Barb to MPT Swivel 	201AB Beaded Hose Barb to MPT 	201BF Hose to Male Flare 
209A Hose Barb to FPT 	209A-SV Hose Barb to FPT Swivel 	209AS Hose Barb to Swivel Ball End 	122AS Swivel Ball Adapter 
209ASF Hose Barb to FM Flare Swivel 	HE1 90° Elbow, Hose to MPT 	HE1-BK 90° Elbow, Hose to MPT 	HE1-FM 90° Elbow, Hose to FPT 
269HB 90° Elbow, Beaded Barb to MPT 	HE1-45 45° Elbow, Hose to MPT 	HM Hose Mender 	HM-90 90° Elbow, Hose to Hose 
HBT2 Hose Barb Tee 	122RWA/122LWA Welding Adapter to Hand Thread 	209RWA/LWA Welding Adapter, Hose x 9/16-18 	BF Hose Crimp On Ferrule 


201A HOSE BARB TO MPT

PART NUMBER	HOSE ID	MPT	A	B	HEX
201A-3A	3/16"	1/8"-27	.69	1.25	1/2"
201A-3B	3/16"	1/4"-18	.69	1.48	9/16"
201A-4A	1/4"	1/8"-27	.97	1.53	1/2"
201A-4B	1/4"	1/4"-18	.97	1.76	9/16"
201A-4C	1/4"	3/8"-18	.97	1.76	11/16"
201A-5A	5/16"	1/8"-27	.97	1.53	1/2"
201A-5B	5/16"	1/4"-18	.97	1.76	9/16"
201A-5C	5/16"	3/8"-18	.97	1.76	11/16"
201A-6A	3/8"	1/8"-27	.97	1.53	1/2"
201A-6B	3/8"	1/4"-18	.97	1.76	9/16"
201A-6C	3/8"	3/8"-18	.97	1.76	11/16"
201A-6D	3/8"	1/2"-14	.97	1.97	7/8"
201A-8B	1/2"	1/4"-18	.97	1.76	9/16"
201A-8C	1/2"	3/8"-18	.97	1.76	11/16"
201A-8D	1/2"	1/2"-14	.97	1.97	7/8"
201A-8E	1/2"	3/4"-14	.97	1.97	1 1/16"
201A-10C	5/8"	3/8"-18	.97	1.76	11/16"
201A-10D	5/8"	1/2"-14	.97	1.97	7/8"
201A-10E	5/8"	3/4"-14	.97	1.97	1 1/16"
201A-12D	3/4"	1/2"-14	.97	1.97	7/8"
201A-12E	3/4"	3/4"-14	.97	1.97	1 1/16"
201A-12F	3/4"	1"-11 1/2	1.19	2.53	1 3/8"
201A-16E	1"	3/4"-14	1.19	2.19	1 1/16"
201A-16F	1"	1"-11 1/2	1.19	2.53	1 3/8"
201A-20E	1 1/4"	3/4"-14	1.19	2.28	1 3/8"
201A-20F	1 1/4"	1"-11 1/2	1.19	2.53	1 3/8"




201AB BEADED HOSE BARB TO MPT

PART NUMBER	HOSE ID	MPT	A	B	HEX
201AB-4A	1/4"	1/8"-27	.62	1.18	1/2"
201AB-4B	1/4"	1/4"-18	.62	1.41	9/16"
201AB-5A	5/16"	1/8"-27	.62	1.18	1/2"
201AB-5B	5/16"	1/4"-18	.62	1.41	9/16"
201AB-6A	3/8"	1/8"-27	.87	1.43	1/2"
201AB-6B	3/8"	1/4"-18	.87	1.67	9/16"
201AB-6C	3/8"	3/8"-18	.87	1.67	11/16"
201AB-8C	1/2"	3/8"-18	.87	1.67	11/16"
201AB-8D	1/2"	1/2"-14	.87	1.88	7/8"
201AB-10D	5/8"	1/2"-14	.87	1.88	7/8"
201AB-10E	5/8"	3/4"-14	.87	1.88	1 1/16"
201AB-12D	3/4"	1/2"-14	.87	1.88	7/8"
201AB-12E	3/4"	3/4"-14	.87	1.88	1 1/16"




201BF HOSE BARB TO MALE FLARE

PART NUMBER	HOSE ID	FLARE THREAD	A	B	HEX
201BF-33	3/16"	3/16"	1.50	.75	7/16"
201BF-44	1/4"	1/4"	1.75	.75	1/2"
201BF-45	1/4"	5/16"	1.75	.75	1/2"
201BF-46	1/4"	3/8"	1.84	.87	5/8"
201BF-55	5/16"	5/16"	1.84	.87	5/8"
201BF-66	3/8"	3/8"	1.84	.87	5/8"
201BF-68	3/8"	1/2"	1.97	.97	3/4"
201BF-88	1/2"	1/2"	1.95	.92	7/8"




201A-SV HOSE BARB TO MPT SWIVEL

PART NUMBER	HOSE ID	MPT	A	B	HEX
201A-3A-SV	3/16"	1/8"-27	.69	1.48	1/2"
201A-4A-SV	1/4"	1/8"-27	.97	1.76	1/2"
201A-4B-SV	1/4"	1/4"-18	.97	1.80	9/16"
201A-5B-SV	5/16"	1/4"-18	.97	1.80	9/16"
201A-6B-SV	3/8"	1/4"-18	.97	1.80	9/16"
201A-6C-SV	3/8"	3/8"-18	.97	1.80	3/4"
201A-6D-SV	3/8"	1/2"-14	.97	2.00	7/8"
201A-8C-SV	1/2"	3/8"-18	.97	1.80	3/4"
201A-8D-SV	1/2"	1/2"-14	.97	2.00	7/8"
201A-12E-SV	3/4"	3/4"-14	.97	2.15	1 1/8"




209A HOSE BARB TO FPT

PART NUMBER	HOSE ID	FPT	A	B	HEX
209A-4A	1/4"	1/8"-27	.97	1.45	1/2"
209A-4B	1/4"	1/4"-18	.97	1.61	5/8"
209A-4C	1/4"	3/8"-18	.97	1.63	3/4"
209A-5A	5/16"	1/8"-27	.97	1.45	1/2"
209A-5B	5/16"	1/4"-18	.97	1.61	5/8"
209A-5C	5/16"	3/8"-18	.97	1.63	3/4"
209A-6A	3/8"	1/8"-27	.97	1.45	1/2"
209A-6B	3/8"	1/4"-18	.97	1.61	5/8"
209A-6C	3/8"	3/8"-18	.97	1.63	3/4"
209A-6D	3/8"	1/2"-14	.97	1.77	15/16"
209A-8B	1/2"	1/4"-18	.97	1.61	5/8"
209A-8C	1/2"	3/8"-18	.97	1.63	3/4"
209A-8D	1/2"	1/2"-14	.97	1.77	15/16"
209A-10C	5/8"	3/8"-18	.97	1.63	3/4"
209A-10D	5/8"	1/2"-14	.97	1.77	15/16"
209A-12D	3/4"	1/2"-14	.97	1.77	15/16"
209A-12E	3/4"	3/4"-14	.97	1.77	1 1/8"
209A-16E	1"	3/4"-14	.97	1.77	1 1/8"





209AS HOSE BARB TO SWIVEL BALL END

PART NUMBER	HOSE ID	FPT	A	B	HEX
209AS-4B	1/4"	1/4"-18	.97	1.56	5/8"
209AS-5B	5/16"	1/4"-18	.97	1.56	5/8"
209AS-6B	3/8"	1/4"-18	.97	1.56	5/8"
209AS-6C	3/8"	3/8"-18	.97	1.62	9/16"
209AS-8C	1/2"	3/8"-18	.97	1.62	3/4"
209AS-8D	1/2"	1/2"-18	.97	1.73	15/16"
209AS-12E	3/4"	3/4"-14	.97	1.73	1 1/8"




122AS SWIVEL BALL ADAPTER

PART NUMBER	MALE N.P.S.M.	MPT	A	HEX
122AS-4A	1/4"	1/8"-27	.91	9/16"
122AS-4B	1/4"	1/4"-18	1.02	9/16"
122AS-6B	3/8"	1/4"-18	1.02	11/16"
122AS-6C	3/8"	3/8"-18	1.09	11/16"
122AS-8C	1/2"	3/8"-18	1.19	27/32"
122AS-8D	1/2"	1/2"-14	1.39	27/32"




209A-SV HOSE BARB TO FPT SWIVEL

PART NUMBER	HOSE ID	FPT	A	B	HEX
209A-3A-SV	3/16"	1/8"-27	.69	1.45	1/2"
209A-4A-SV	1/4"	1/8"-27	.97	1.73	1/2"
209A-4B-SV	1/4"	1/4"-18	.97	1.80	5/8"
209A-5B-SV	5/16"	1/4"-18	.97	1.80	5/8"
209A-6B-SV	3/8"	1/4"-18	.97	1.80	5/8"
209A-6C-SV	3/8"	3/8"-18	.97	1.82	3/4"
209A-6D-SV	3/8"	1/2"-14	.97	1.86	15/16"
209A-8C-SV	1/2"	3/8"-18	.97	1.82	3/4"
209A-8D-SV	1/2"	1/2"-14	.97	1.86	15/16"



209ASF HOSE BARB TO FEMALE FLARE SW


PART NUMBER	HOSE ID	FLARE THREAD	A	HEX
209ASF-44	1/4"	7/16"-20	.97	9/16"
209ASF-45	1/4"	1/2"-20	.97	5/8"
209ASF-55	5/16"	1/2"-20	.97	5/8"
209ASF-68	3/8"	3/4"-16	.97	7/8"
209ASF-88	1/2"	3/4"-16	.97	7/8"
209ASF-810	1/2"	7/8"-14	.97	1"
209ASF-1010	5/8"	7/8"-14	.97	1"
209ASF-1210	3/4"	7/8"-14	.97	1"



*Female Flare is a dual angle seat, accepting both 37°/45°

209ASF-45° HOSE BARB TO FEMALE FLARE SWIVEL


PART NUMBER	HOSE ID	FLARE THREAD	A	HEX
209ASF-46-45°	1/4"	5/8"-18	.97	3/4"
209ASF-56-45°	5/16"	5/8"-18	.97	3/4"
209ASF-66-45°	3/8"	5/8"-18	.97	3/4"
209ASF-1212-45°	3/4"	1 1/16"-14	.97	1 1/4"



*Flare accepts 45° mating part only

209ASF-37° HOSE BARB TO FEMALE FLARE SWIVEL


PART NUMBER	HOSE ID	FLARE THREAD	A	HEX
209ASF-46-37°	1/4"	9/16"-18	.97	11/16"
209ASF-56-37°	5/16"	9/16"-18	.97	11/16"
209ASF-66-37°	3/8"	9/16"-18	.97	11/16"
209ASF-1212-37°	3/4"	1 1/16"-12	.97	1 1/4"



*Flare accepts 37° mating part only

HE1 90° ELBOW, HOSE TO MPT

PART NUMBER	HOSE ID	MPT	A
HE1-3B	3/16"	1/4"-18	0.95
HE1-4A	1/4"	1/8"-27	0.781
HE1-4B	1/4"	1/4"-18	1.00
HE1-4C	1/4"	3/8"-18	1.00
HE1-5A	5/16"	1/8"-27	0.764
HE1-5B	5/16"	1/4"-18	1.00
HE1-5C	5/16"	3/8"-18	1.09
HE1-6A	3/8"	1/8"-27	0.70
HE1-6B	3/8"	1/4"-18	0.86
HE1-6C	3/8"	3/8"-18	1.00
HE1-6D	3/8"	1/2"-14	1.28
HE1-8B	1/2"	1/4"-18	0.95
HE1-8C	1/2"	3/8"-18	1.08
HE1-8D	1/2"	1/2"-14	1.22
HE1-10C	5/8"	3/8"-18	1.13
HE1-10D	5/8"	1/2"-14	1.21
HE1-12E	3/4"	3/4"-14	1.31
HE1-16F	1"	1"-11.5"	1.75



*Forged Style




*Barstock Style

Add a "BK" to the end of the part number

Ex: HE1-4A-BK


HE1-FM 90° ELBOW, HOSE TO FPT

PART NUMBER	HOSE ID	FPT	A	B
HE1-4A-FM	1/4"	1/8"-27	1.05	.79
HE1-4B-FM	1/4"	1/4"-18	1.14	.79
HE1-6A-FM	3/8"	1/8"-27	1.33	.97
HE1-6B-FM	3/8"	1/4"-18	1.33	.97
HE1-6C-FM	3/8"	3/8"-18	1.33	.97
HE1-8B-FM	1/2"	1/4"-18	1.64	.97
HE1-8C-FM	1/2"	3/8"-18	1.64	.97
HE1-8D-FM	1/2"	1/2"-14	1.64	.97
HE1-12E-FM	3/4"	3/4"-14	1.52	.97




269HB 90° ELBOW, BEADED BARB TO MPT

PART NUMBER	HOSE ID	MPT	A	B	C
269HB-6-6	3/8"	3/8"-18	1.19	.78	.88
269HB-8-4	1/2"	1/4"-18	1.16	.78	.99
269HB-8-6	1/2"	3/8"-18	1.16	.78	1.08
269HB-8-8	1/2"	1/2"-14	1.28	.78	1.25
269HB-10-4	5/8"	1/4"-18	1.13	.78	.99
269HB-10-6	5/8"	3/8"-18	1.16	.78	.99
269HB-10-8	5/8"	1/2"-14	1.28	.78	1.25
269HB-12-8	3/4"	1/2"-14	1.28	.78	1.25
269HB-12-12	3/4"	3/4"-14	1.33	.78	1.27




HE1-45 45° ELBOW, HOSE TO MPT

PART NUMBER	HOSE ID	MPT
HE1-45-4A	1/4"	1/8"-27
HE1-45-5A	5/16"	1/8"-27
HE1-45-5B	5/16"	1/4"-18
HE1-45-6A	3/8"	1/8"-27
HE1-45-6B	3/8"	1/4"-18
HE1-45-6C	3/8"	3/8"-18
HE1-45-8B	1/2"	1/4"-18
HE1-45-8C	1/2"	3/8"-18
HE1-45-10C	5/8"	3/8"-18




HM HOSE MENDER

PART NUMBER	HOSE ID	A
HM-2	1/8"	1.09
HM-3	3/16"	1.65
HM-4	1/4"	2.00
HM-5	5/16"	2.00
HM-6	3/8"	2.00
HM-8	1/2"	2.00
HM-10	5/8"	2.00
HM-12	3/4"	2.00
HM-16	1"	2.00




HM-90 90° HOSE MENDER

PART NUMBER	HOSE ID	A	B
HM-90-2	1/8"	.73	.46
HM-90-3	3/16"	1.05	.79
HM-90-4	1/4"	1.05	.79
HM-90-5	5/16"	1.15	.79
HM-90-6	3/8"	1.15	.79
HM-90-8	1/2"	1.25	.87
HM-90-10	5/8"	1.30	.87
HM-90-12	3/4"	1.41	.89




HBT2 HOSE BARB TEE

PART NUMBER	HOSE ID	A	B
HBT2-2	1/8"	.71	.46
HBT2-3	3/16"	.94	.71
HBT2-4	1/4"	.94	.71
HBT2-5	5/16"	1.18	.79
HBT2-6	3/8"	1.26	.86
HBT2-8	1/2"	1.26	.86
HBT2-10	5/8"	1.33	.90
HBT2-12	3/4"	1.41	.90



122RWA WELDING ADAPTER 9/16-18 RH

PART NUMBER	MPT	RH THREAD
122RWA-B	1/4"	9/16-18 RH
122RWA-C	3/8"	9/16-18 RH




209RWA HOSE TO 9/16-18 RH

PART NUMBER	HOSE I.D.	THREAD	HEX
209RWA-3	3/16"	9/16-18 RH	11/16"
209RWA-4	1/4"	9/16-18 RH	11/16"
209RWA-5	5/16"	9/16-18 RH	11/16"
209RWA-6	3/8"	9/16-18 RH	11/16"



122LWA HOSE TO 9/16-18 LH

PART NUMBER	PIPE	LH THREAD
122LWA-B	1/4"	9/16-18 LH
122LWA-C	3/8"	9/16-18 LH




209LWA HOSE TO 9/16-18 LH

PART NUMBER	HOSE I.D.	LH THREAD	HEX
209RWA-3	3/16"	9/16-18 LH	11/16"
209RWA-4	1/4"	9/16-18 LH	11/16"
209RWA-5	5/16"	9/16-18 LH	11/16"
209RWA-6	3/8"	9/16-18 LH	11/16"



BF CRIMP ON FERRULE

Part Number	Cross Ref.	I.D.	Length (A)	Hole (B)	Thickness	Corresponding Barb Sizes
BF-.478-.687.328	4750	0.478	0.687	0.328	0.025	3/16"
BF-.500-1.00-.343	7322	0.5	1	0.343	0.025	3/16"
BF-.500-.500-.343	624	0.5	0.5	0.343	0.02	3/16"
BF-.525-1.00-.375	7323	0.525	1	0.375	0.025	1/4"
BF-.525-1.00-.437	9974	0.525	1	0.437	0.025	1/4"
BF-.525-.470-.360	625	0.525	0.47	0.36	0.02	1/4"
BF-.531-1.00-.375	7324	0.531	1	0.375	0.025	1/4"
BF-.560-.750-.375	3588	0.56	0.75	0.375	0.02	1/4"
BF-.593-1.00-.437	7326	0.593	1	0.437	0.025	5/16"
BF-.600-.500-.500	JJ	0.6	0.5	0.5	0.02	5/16"
BF-.625-.500-.500	II	0.625	0.5	0.5	0.02	5/16"
BF-.625-1.00-.437	7327	0.625	1	0.437	0.025	3/8"
BF-.650-.500-.500	HH	0.65	0.5	0.5	0.02	3/8"
BF-.656-1.00-.437	7328	0.656	1	0.437	0.025	3/8"
BF-.675-.515-.500	GG	0.675	0.515	0.5	0.02	3/8"
BF-.690-1.00-.500	7329	0.69	1	0.5	0.025	3/8"
BF-.725-.530-.500	EE	0.725	0.53	0.5	0.02	3/8"
BF-.750-.531-.500	DD	0.75	0.531	0.5	0.02	3/8"
BF-.750-1.00-.625	7331	0.75	1	0.625	0.025	1/2"
BF-.775-.531-.500	CC	0.775	0.531	0.5	0.02	3/8"
BF-.781-1.00-.625	7332	0.781	1	0.625	0.025	1/2"
BF-.812-1.00-.625	7333	0.812	1	0.625	0.025	1/2"
BF-.937-.875-.750	7242	0.937	0.875	0.75	0.025	5/8"
BF-.975-.843-.687	5028A	0.975	0.843	0.687	0.025	5/8"
BF-1.025-.843-.687	7114A	1.025	0.843	0.687	0.025	5/8"
BF-1.150-.843-.875	7104A	1.15	0.843	0.875	0.025	3/4"
BF-1.175-.875-.875	7088A	1.175	0.875	0.875	0.025	3/4"
BF-1.500-.875-1.125	1500	1.5	0.875	1.125	0.025	1"



Please note that "Corresponding Barb Sizes" is a recommendation provided by Robo-Fit based on commonly used industry specifications. However, it is important to understand that Robo-Fit does not take responsibility for the accuracy or suitability of this recommendation. It is the user's responsibility to ensure that the selected combination of hose and fittings is appropriate for their intended application and meets all relevant safety standards and regulations. Robo-Fit strongly advises users to seek professional guidance and perform appropriate testing to verify the compatibility and integrity of any assembly. By using Robo-Fit products, you acknowledge and agree to assume full responsibility for the proper selection, installation, and use of all components.



BRASS PUSH-LOK HOSE BARBS

CONSTRUCTION	• CA360, CA345, CA3604, CA377 Brass 
APPLICATIONS	• Use with thermoplastic or rubber push-lock hose. No use of hose clamp or crimped type fitting required. 
RANGES	• Temperature Range: -30° to +180° F. 




PUSH-LOK FITTING ASSEMBLY

1. Make a clean square cut on your hose end.
2. Use lubricant on the end of the hose.
3. Move the fitting into the hose so only one barb is inserted into the hose. Make sure the fitting is lined up properly with the hose.
4. Push the fitting fully into the hose so that the end of the hose is covered by the yellow plastic cap. Make sure the fitting is fully inserted before use.

ORDERING INFORMATION



- Parts that include “PBF” are supplied as low lead compliant fittings.
- Part numbers without the “PBF” distinction are NOT lead free compliant.
- Nomenclature Example:



NOTES



- Non-stock items and special parts are available on a quotation basis.
- Configurations and dimensions are subject to change without notice.

⚠ WARNING: Products offered by Robo-Fit can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov

301 Hose Barb to MPT 	301-SV Hose Barb to MPT Swivel 	302 Hose Barb to 45° Male Flare 	303 Rigid Tube Shank 
304 Hose Splicer 	305 Hose Barb to Inverted Flare 	306 Hose Barb to Inverted Flare 	307 Hose to 45° Flare, Swivel 
308 Hose to 37° Flare, Swivel 	309 Hose to Dual Angle, 45°/37° 	3099 Hose Barb to Female Pipe 	3099-SV Hose Barb to FPT Swivel 
310 Hose Barb to Male 37° Flare 	1000B 90° Hose Barb to Male Pipe 		


301 HOSE BARB TO MPT

PART NUMBER	HOSE ID	MPT	A	B	HEX
301-42	1/4"	1/8"-27	.87	1.43	1/2"
301-44	1/4"	1/4"-18	.87	1.66	9/16"
301-46	1/4"	3/8"-18	.87	1.66	11/16"
301-52	5/16"	1/8"-27	.87	1.43	1/2"
301-54	5/16"	1/4"-18	.87	1.66	9/16"
301-62	3/8"	1/8"-27	.97	1.53	1/2"
301-64	3/8"	1/4"-18	.97	1.76	9/16"
301-66	3/8"	3/8"-18	.97	1.76	11/16"
301-68	3/8"	1/2"-14	.97	1.97	7/8"
301-84	1/2"	1/4"-18	.97	1.76	11/16"
301-86	1/2"	3/8"-18	.97	1.76	11/16"
301-88	1/2"	1/2"-14	.97	1.97	7/8"
301-812	1/2"	3/4"-14	.97	1.97	1 1/16"
301-108	5/8"	1/2"-14	1.45	2.45	7/8"
301-1012	5/8"	3/4"-14	1.45	2.45	1 1/16"
301-128	3/4"	1/2"-14	1.45	2.45	7/8"
301-1212	3/4"	3/4"-14	1.45	2.45	1 1/16"




302 HOSE BARB TO 45° MALE FLARE

PART NUMBER	HOSE ID	FLARE THREAD	A	B	HEX
302-44	1/4"	1/4"	1.56	.75	7/16"
302-45	1/4"	5/16"	1.66	.84	1/2"
302-66	3/8"	3/8"	1.75	.94	5/8"
302-88	1/2"	1/2"	1.94	1.00	3/4"




303 RIGID TUBE SHANK

PART NUMBER	HOSE ID	TUBE ID	A	B
303-43	1/4"	3/16"	1.94	1.12
303-44	1/4"	1/4"	2.00	1.19
303-45	1/4"	5/16"	2.03	1.22
303-66	3/8"	3/8"	2.16	1.34
303-88	1/2"	1/2"	2.44	1.48
303-1010	5/8"	5/8"	2.61	1.54





301-SV HOSE BARB TO MPT SWIVEL

PART NUMBER	HOSE ID	MPT	A	B	HEX
301-44-SV	1/4"	1/4"-18	.87	1.71	9/16"
301-54-SV	5/16"	1/4"-18	.87	1.71	9/16"
301-64-SV	3/8"	1/4"-18	.97	2.00	9/16"
301-66-SV	3/8"	3/8"-18	.97	2.00	11/16"
301-86-SV	1/2"	3/8"-18	.97	2.00	11/16"
301-88-SV	1/2"	1/2"-14	.97	2.00	7/8"




304 HOSE SPLICER

PART NUMBER	HOSE ID	A	B
304-44	1/4"	.87	1.80
304-55	5/16"	.87	1.80
304-66	3/8"	.97	2.00
304-88	1/2"	.97	2.00
304-1010	5/8"	1.45	3.03
304-1212	3/4"	1.45	3.03




305 HOSE BARB TO INVERTED FLARE

PART NUMBER	HOSE ID	INV FLARE THREAD	HEX
305-43	1/4"	3/16"	3/8"
305-44	1/4"	1/4"	7/16"
305-45	1/4"	5/16"	1/2"
305-55	5/16"	5/16"	1/2"
305-66	3/8"	3/8"	5/8"
305-88	1/2"	1/2"	3/4"
305-1010	5/8"	5/8"	7/8"




308 HOSE TO FEMALE 37° FLARE, SWIVEL

PART NUMBER	HOSE ID	FLARE THREAD	A	HEX
308-46	1/4"	9/16"-18	.87	11/16"
308-56	5/16"	9/16"-18	.87	11/16"
308-66	3/8"	9/16"-18	.97	11/16"
308-1212	3/4"	1-1/16"-12	1.45	1 1/4"




306 HOSE BARB TO INVERTED FEMALE FLARE

PART NUMBER	HOSE ID	INV FLARE THREAD	HEX
306-43	1/4"	3/16"	7/16"
306-44	1/4"	1/4"	1/2"
306-45	1/4"	5/16"	9/16"
306-66	3/8"	3/8"	3/4"
306-88	1/2"	1/2"	7/8"




309 HOSE TO DUAL ANGLE, SWIVEL, 45°/37°

PART NUMBER	HOSE ID	FLARE THREAD	A	HEX
309-44	1/4"	7/16"-20	.87	9/16"
309-45	1/4"	1/2"-20	.87	5/8"
309-55	5/16"	1/2"-20	.87	5/8"
309-68	3/8"	3/4"-16	.97	7/8"
309-88	1/2"	3/4"-16	.97	7/8"
309-810	1/2"	7/8"-14	.97	1"
309-108	5/8"	3/4"-16	1.45	7/8"
309-1010	5/8"	7/8"-14	1.45	1"
309-1210	3/4"	7/8"-14	1.45	1"




307 HOSE TO FEMALE 45° FLARE, SWIVEL

PART NUMBER	HOSE ID	FLARE THREAD	HEX	A
307-46	1/4"	5/8"-18"	3/4"	.87
307-56	5/16"	5/8"-18"	3/4"	.87
307-66	3/8"	5/8"-18"	3/4"	.97
307-1212	3/4"	1 1/16"-14	1 1/4"	1.45




3099 HOSE TO FEMALE PIPE

PART NUMBER	HOSE ID	FPT	A	B	HEX
3099-42	1/4"	1/8"-27	.87	1.35	1/2"
3099-44	1/4"	1/4"-18	.87	1.51	5/8"
3099-46	1/4"	3/8"-18	.87	1.53	3/4"
3099-52	5/16"	1/8"-27	.87	1.35	1/2"
3099-54	5/16"	1/4"-18	.87	1.51	5/8"
3099-62	3/8"	1/8"-27	.97	1.45	1/2"
3099-64	3/8"	1/4"-18	.97	1.61	5/8"
3099-66	3/8"	3/8"-18	.97	1.63	3/4"
3099-68	3/8"	1/2"-14	.97	1.77	15/16"
3099-84	1/2"	1/4"-18	.97	1.61	5/8"
3099-86	1/2"	3/8"-18	.97	1.63	3/4"
3099-88	1/2"	1/2"-14	.97	1.77	15/16"
3099-812	1/2"	3/4"-14	.97	1.77	1 1/8"
3099-108	5/8"	1/2"-14	1.45	2.25	15/16"
3099-1012	5/8"	3/4"-14	1.45	2.25	1 1/8"
3099-128	3/4"	1/2"-14	1.45	2.25	15/16"
3099-1212	3/4"	3/4"-14	1.45	2.25	1 1/8"




310 HOSE TO JIC MALE 37°

PART NUMBER	HOSE ID	37° Male Flare	A	HEX
310-44	1/4"	7/16"-20	1.57	1/2"
310-45	1/4"	1/2"-20	1.60	9/16"
310-66	3/8"	9/16"-18	1.60	9/16"
310-88	1/2"	3/4"-16	1.97	3/4"




3099-SV HOSE BARB TO FPT, SWIVEL

PART NUMBER	HOSE ID	FPT	A	HEX
3099-44-SV	1/4"	1/4"-18	.87	5/8"
3099-54-SV	5/16"	1/4"-18	.87	5/8"
3099-64-SV	3/8"	1/4"-18	.97	5/8"
3099-86-SC	1/2"	3/8"-18	.97	3/4"
3099-88-SV	1/2"	1/2"-14	.97	15/16"



1000B 90° HOSE BARB TO MPT

PART NUMBER	HOSE ID	MPT	A	B
10004B-C02	1/4"	1/8"-27	1.22	.82
10004B-C04	1/4"	1/4"-18	1.40	.82
10005B-C02	5/16"	1/8"-27	1.08	.87
10005B-C04	5/16"	1/4"-18	1.15	.87
10006B-C02	3/8"	1/8"-27	1.35	.92
10006B-C04	3/8"	1/4"-18	1.40	.92
10006B-C06	3/8"	3/8"-18	1.51	.92
10008B-C06	1/2"	3/8"-18	1.54	1.02
10008B-C08	1/2"	1/2"-14	1.61	1.02
10012B-C08	3/4"	1/2"-14	2.15	1.50
10012B-C12	3/4"	3/4"-14	2.23	1.50





BRASS FLARE FITTINGS

CONSTRUCTION

- CA360, CA345, CA3604, CA377 Brass



APPLICATIONS

- Compatible with copper, brass, aluminum and steel hydraulic tubing that can be flared

RANGES

Temperature Range: -65° to +250° F.

Pressure Range:

Maximum working pressure (PSI) depends on the tubing material, O.D. wall thickness and fitting.




Flare Fitting Assembly:

1. Make sure the tubing is cut squarely with a tube cutter. After cutting, make sure the tube is clean and free of burrs.
2. Move the flare nut over of the tubing.
3. Flare the end of the tubing with a flaring tubing. Most brass applications require a 45° flare.
4. Screw the nut and the connecting fitting together hand tight. Then tighten with a wrench 1/4 to 1/2 turn past hand-tight. There should be a metal to metal seal.



ORDERING INFORMATION








- Parts that include "PBF" are supplied as low lead compliant fittings.
- Part numbers without the "PBF" distinction are NOT lead free compliant.
- Nomenclature Example:



NOTES


- Non-stock items and special parts are available on a quotation basis.
- Configurations and dimensions are subject to change without notice.



B1 Bonnet 	B2 Gasket 	C1 Cross Tube All Ends 	DE3 Drop Ear Elbow 	E1 90° Male Flare Elbow 	RE1 (SAE) 90° Male Flare Elbow 
E1-45 45° Male Elbow 	E2 90° Union Elbow 	ER2 90° Reducing Elbow 	E3 90° Female Flare Elbow 	E4 90° Tube to Female Flare 	ES4 90° Tube to FM Swivel 
K1 Cylinder Valve Adapter 	41AS (SAE) Machined Nut 	NSE1 Extra Short Nut 	N1 Machined Short Nut 	N2 (SAE) Machined Long Nut 	N4 (SAE) Forged Long Nut 
NS4 Forged Short Nut 	RNS4 (SAE) Forged Short Nut 	NS4R Forged Reducing Nut 	N5 Flare Cap 	P2 Flare Plug 	T1 Flare Branch Tee 
T2 Flare Union Tee 	RT2 (SAE) Flare Union Tee 	TR2 Reducing Union Tee 	T3 Flare Run Tee 	T4 Flare Street Tee 	U1 Male Flare Connector 
RU1 (SAE) Male Flare Connector 	U2 Flare Union 	RU2 (SAE) Flare Union 	UR2 Union Reducer 	RUR2 (SAE) Union Reducer 	UR3 Reducer FM to M Flare 
U3 Flare to FPT 	RU3 (SAE) Flare to FPT 	US3 Flare to Solder 	U4 Flare Connector 	US4 Swivel Flare Connector 	


B1 BONNET

PART NUMBER	O.D. TUBE	A
B1-4	1/4"	.35
B1-6	3/8"	.54
B1-8	1/2"	.65
B1-10	5/8"	.76





B2 GASKET

PART NUMBER	O.D. TUBE	A
B2-4	1/4"	.35
B2-6	3/8"	.54
B2-8	1/2"	.65
B2-10	5/8"	.76
B2-12	3/4"	.94




C1 CROSS TUBE ALL ENDS

PART NUMBER	O.D. TUBE	A	B
C1-4444	1/4"	.89	.89
C1-6666	3/8"	1.00	1.00
C1-8888	1/2"	1.12	1.12
C1-10101010	5/8"	1.43	1.43




DE3 DROP EAR ELBOW

PART NUMBER	O.D. TUBE	FPT	A	B
DE3-6D	3/8"	1/2"	1.23	1.38
DE3-8D	1/2"	1/2"	1.31	1.38



E1 90° MALE FLARE ELBOW

PART NUMBER	O.D. TUBE	MPT	A	B
E1F-2A	1/8"	1/8"	.62	.68
E1F-3A	3/16"	1/8"	.76	.76
E1-3A	3/16"	1/8"	.75	.75
E1F-3B	3/16"	1/4"	.80	.89
E1F-4A	1/4"	1/8"	.81	.78
E1-4A	1/4"	1/8"	.81	.78
E1F-4B	1/4"	1/4"	.81	.88
E1-4B	1/4"	1/4"	.91	.93
E1F-4C	1/4"	3/8"	.97	.95
E1-4C	1/4"	3/8"	.91	1.04
E1F-4D	1/4"	1/2"	1.03	1.09
E1F-5A	5/16"	1/8"	.93	.84
E1-5A	5/16"	1/8"	.91	.84
E1F-5B	5/16"	1/4"	.93	.88
E1F-5C	5/16"	3/8"	.97	.91
E1F-6A	3/8"	1/8"	.97	.91
E1F-6B	3/8"	1/4"	.97	1.04
E1-6B	3/8"	1/4"	.97	1.04
E1F-6C	3/8"	3/8"	1.00	.91
E1-6C	3/8"	3/8"	1.05	1.04
E1F-6D	3/8"	1/2"	1.09	1.09
E1F-6E	3/8"	3/4"	1.25	1.19
E1F-8B	1/2"	1/4"	1.19	1.00
E1-8B	1/2"	1/4"	1.16	1.09
E1F-8C	1/2"	3/8"	1.19	1.00
E1-8C	1/2"	3/8"	1.16	1.09




Barstock Style



Forged Style



E1 90° MALE FLARE ELBOW

PART NUMBER	O.D. TUBE	MPT	A	B
E1F-8D	1/2"	1/2"	1.12	1.15
E1-8D	1/2"	1/2"	1.16	1.25
E1F-8E	1/2"	3/4"	1.41	1.25
E1F-10B	5/8"	1/4"	1.58	1.54
E1-10C	5/8"	3/8"	1.34	1.12
E1F-10D	5/8"	1/2"	1.28	1.29
E1-10D	5/8"	1/2"	1.34	1.22
E1F-10E	5/8"	3/4"	1.38	1.31
E1F-12C	3/4"	3/8"	1.62	1.44
E1F-12D	3/4"	1/2"	1.66	1.50
E1F-12E	3/4"	3/4"	1.66	1.62
E1F-14E	7/8"	3/4"	1.69	1.78
E1F-16E	1"	3/4"	1.93	2.04
E1F-16F	1"	1"	1.93	1.77



E1-45 45° MALE FLARE ELBOW


PART NUMBER	O.D. TUBE	MPT	A	B
E1-45-4A	1/4"	1/8"	.64	.67
E1-45-4B	1/4"	1/4"	.86	.75
E1-45-5A	5/16"	1/8"	.67	.78
E1-45-5B	5/16"	1/4"	.86	.81
E1-45-6B	3/8"	1/4"	.86	.89
E1-45-6C	3/8"	3/8"	.86	.89
E1-45-6D	3/8"	1/2"	1.05	1.08
E1-45-8C	1/2"	3/8"	1.10	1.10
E1-45-8D	1/2"	1/2"	1.20	1.44
E1-45-10C	5/8"	3/8"	1.19	.97
E1-45-10D	5/8"	1/2"	1.17	1.23
E1-45-12D	3/4"	1/2"	1.30	1.10
E1-45-12E	3/4"	3/4"	1.28	1.19



REF SAE o10201


RE1 90° MALE FLARE ELBOW

PART NUMBER	O.D. TUBE	MPT	A	B
RE1-4A	1/4"	1/8"	.82	.78
RE1-4B	1/4"	1/4"	.91	.94
RE1-4C	1/4"	3/8"	.94	1.03
RE1-5A	5/16"	1/8"	.91	.78
RE1-5B	5/16"	1/4"	.97	.94
RE1-6A	3/8"	1/8"	1.03	.91
RE1-6B	3/8"	1/4"	1.00	1.06
RE1-6C	3/8"	3/8"	1.06	1.09
RE1-6D	3/8"	1/2"	1.16	1.28
RE1-8B	1/2"	1/4"	1.22	1.12
RE1-8C	1/2"	3/8"	1.25	1.19
RE1-8D	1/2"	1/2"	1.28	1.38
RE1-8E	1/2"	3/4"	1.41	1.41
RE1-10C	5/8"	3/8"	1.41	1.25
RE1-10D	5/8"	1/2"	1.41	1.38
RE1-10E	5/8"	3/4"	1.47	1.50



E2 90° UNION FLARE ELBOW

PART NUMBER	O.D. TUBE	A
E2-2	1/8"	.63
E2-3	3/16"	.71
E2-4	1/4"	.81
E2-5	5/16"	.94
E2-6	3/8"	1.00
E2-8	1/2"	1.22
E2-10	5/8"	1.41
E2-12	3/4"	1.65
E2-14	7/8"	1.87




REF SAE o10302

REF SAE o10202

ER2 90° REDUCING ELBOW

PART NUMBER	O.D. TUBE	A	B
ER2-64	3/8"X1/4"	1.00	.91
ER2-84	1/2"X1/4"	1.19	.98
ER2-86	1/2"X3/8"	1.19	1.00
ER2-106	5/8"X3/8"	1.24	1.12
ER2-108	5/8"X1/2"	1.36	1.22

REF SAE 010201




E4 90° TUBE TO FEMALE FLARE

PART NUMBER	O.D. TUBE	A	B
E4F-44	1/4"	.96	.72
E4F-66	3/8"	1.05	.80

*Use with B2 Series


(Copper Gasket)



E3 90° FEMALE FLARE ELBOW

PART NUMBER	O.D. TUBE	MPT	A	B
E3F-3A	3/16"	1/8"	.88	.48
E3F-4A	1/4"	1/8"	1.00	.62
E3F-4B	1/4"	1/4"	.97	.59
E3F-4C	1/4"	3/8"	1.00	.75
E3F-5A	5/16"	1/8"	1.02	.60
E3F-5B	5/16"	1/4"	1.02	.67
E3F-6A	3/8"	1/8"	1.06	.88
E3F-6B	3/8"	1/4"	1.06	.93
E3-6B	3/8"	1/4"	1.03	.69
E3F-6D	3/8"	1/2"	1.16	.66
E3F-6E	3/8"	3/4"	1.28	.72
E3F-8B	1/2"	1/4"	1.19	1.00
E3F-8C	1/2"	3/8"	1.20	.65
E3-8C	1/2"	3/8"	1.25	.70
E3F-8D	1/2"	1/2"	1.28	.72
E3F-8E	1/2"	3/4"	1.41	.72
E3F-10C	5/8"	3/8"	1.34	1.22
E3F-10D	5/8"	1/2"	1.38	1.25
E3F-10E	5/8"	3/4"	1.50	1.25
E3F-12D	3/4"	1/2"	1.64	1.31
E3F-12E	3/4"	3/4"	1.84	1.15
E3F-14E	7/8"	3/4"	1.88	1.12


REF SAE 010203



Forged Style

ES4 90° TUBE TO FEMALE FLARE, SWIVEL



PART NUMBER	O.D. TUBE	A	B
ES4-44	1/4"	.81	1.15
ES4-66	3/8"	1.05	1.34
ES4-88	1/2"	1.26	1.54



K1 CYLINDER ADAPTER

PART NUMBER	O.D. TUBE	FPT	A	HEX
K1-1	1/4"	3/4"	1.12	1-1/8"
K1-8	1/4"	1/2"	1.12	1-1/4"


REF SAE 010165



41AS MACHINED NUT (SAE 010110)

PART NUMBER	O.D. TUBE	A	HEX
41AS-6	3/8"	1.00	3/4"
41AS-8	1/2"	1.12	7/8"
41AS-10	5/8"	1.31	1-1/16"


REF SAE 010302



N2 MACHINED LONG NUT


PART NUMBER	O.D. TUBE	A	HEX
N1-2	1/8"	.75	3/8"
N1-3	3/16	.81	7/16"
N1-4	1/4"	.94	9/16"
N1-5	5/16"	1.12	5/8"
N1-6	3/8"	1.31	3/4"
N1-8	1/2"	1.62	7/8"
N1-10	5/8"	1.88	1-1/16"
N1-12	3/4"	2.19	1-1/4"

REF SAE 010111



NSE1 MACHINED NUT EXTRA SHORT


PART NUMBER	O.D. TUBE	A	HEX
NSE1-4	1/4"	.50	9/16"
NSE1-6	3/8"	.69	3/4"
NSE1-8	1/2"	.81	7/8"



N4 FORGED LONG NUT



PART NUMBER	O.D. TUBE	A	B
N4-4	1/4"	.94	3/4"
N4-6	3/8"	1.06	7/8"
N4-8	1/2"	1.19	1"
N4-10	5/8"	1.44	1-1/8"
N4-12	3/4"	1.75	1-3/8"

REF SAE 010167




N1 MACHINED NUT SHORT

PART NUMBER	O.D. TUBE	A	HEX
N1-2	1/8"	.50	3/8"
N1-3	3/16	.62	7/16"
N1-4	1/4"	.75	9/16"
N1-5	5/16"	.88	5/8"
N1-6	3/8"	.88	3/4"
N1-7	7/16"	1.06	13/16"
N1-8	1/2"	1.00	7/8"
N1-10	5/8"	1.00	1"
N1-12	3/4"	1.50	1-1/4"
N1-14	7/8"	1.18	1-3/8"
N1-16	1"	1.81	1-5/8"



NS4 FORGED SHORT NUT


PART NUMBER	O.D. TUBE	A	HEX
NS4-3	3/16"	.68	1/2"
NS4-4	1/4"	.60	5/8"
NS4-5	5/16"	.63	3/4"
NS4-6	3/8"	.70	13/16"
NS4-8	1/2"	.82	15/16"
NS4-10	5/8"	.95	1-1/16"
NS4-12	3/4"	1.13	1-3/8"
NS4-14	7/8"	1.18	1-3/8"



RNS4 FORGED SHORT NUT



PART NUMBER	O.D. TUBE	A	HEX
RNS4-4	1/4"	.62	3/4"
RNS4-6	3/8"	.72	7/8"
RNS4-8	1/2"	.86	1"
RNS4-10	5/8"	.98	1-1/8"
RNS4-12	3/4"	1.12	1-3/8"

REF SAE 010166




P2 PLUG

PART NUMBER	O.D. TUBE	A	HEX
P2-3	3/16"	.47	1/2"
P2-4	1/4"	.47	1/2"
P2-5	5/16"	.62	5/8"
P2-6	3/8"	.72	11/16"
P2-8	1/2"	.75	13/16"
P2-10	5/8"	.81	15/16"
P2-12	3/4"	1.19	1-3/8"




NSR4 FORGED SHORT REDUCING NUT

PART NUMBER	O.D. TUBE	A	HEX
NSR4-64	3/8"X1/4"	.70	13/16"
NSR4-65	3/8"X5/16"	.70	13/16"
NSR4-86	1/2"X3/8"	.82	15/16"
NSR4-106	5/8"X3/8"	.95	1-1/8"
NSR4-108	5/8"X1/2"	.95	1-1/8"





T1 FLARE MALE BRANCH TEE

PART NUMBER	O.D. TUBE	MPT	A	B
T1F-2A	1/8"	1/8"	.60	.67
T1F-3A	3/16"	1/8"	.74	.77
T1F-4A	1/4"	1/8"	.78	.76
T1-4A	1/4"	1/8"	.81	.82
T1F-4B	1/4"	1/4"	.88	.88
T1F-4C	1/4"	3/8"	.93	.98
T1F-5A	5/16"	1/8"	.90	.79
T1F-5B	5/16"	1/4"	.95	.93
T1F-6A	3/8"	1/8"	1.00	.88
T1-6B	3/8"	1/4"	1.00	.93
T1-6C	3/8"	3/8"	1.00	.98
T1F-6D	3/8"	1/2"	1.14	1.20
T1F-8C	1/2"	3/8"	1.19	1.13
T1-8D	1/2"	1/2"	1.22	1.23
T1F-10C	5/8"	3/8"	1.38	1.23
T1F-10D	5/8"	1/2"	1.41	1.28
T1F-12D	3/4"	1/2"	1.62	1.60
T1F-12E	3/4"	3/4"	1.66	1.42



N5 FLARE CAP


PART NUMBER	O.D. TUBE	A	HEX
N5-3	3/16"	.47	1/2"
N5-4	1/4"	.47	1/2"
N5-5	5/16"	.62	5/8"
N5-6	3/8"	.72	11/16"
N5-8	1/2"	.75	13/16"
N5-10	5/8"	.81	15/16"
N5-12	3/4"	1.19	1-3/8"



REF SAE 010425


T2 FLARE UNION TEE

PART NUMBER	O.D. TUBE	A
T2F-2	1/8"	.71
T2F-3	3/16"	.76
T2F-4	1/4"	.78
T2-4	1/4"	.86
T2F-5	5/16"	.94
T2F-6	3/8"	1.00
T2-6	3/8"	.98
T2-8	1/2"	1.16
T2-10	5/8"	1.41
T2F-12	3/4"	1.62





TR2 REDUCING UNION TEE

PART NUMBER	O.D. TUBE	A	B
TR2-446	1/4"X1/4"X3/8"	.91	1.00
TR2-464	1/4"X3/8"X1/4"	.86	1.00
TR2-466	1/4"X3/8"X3/8"	.98	.98
TR2-664	3/8"X3/8"X1/4"	1.00	.88
TR2-668	3/8"X3/8"X1/2"	1.00	1.19
TR2-6610	3/8"X3/8"X5/8"	1.25	1.44
TR2-686	3/8"X1/2"X3/8"	1.05	1.16
TR2-6106	3/8"X5/8"X3/8"	1.22	1.16
TR2-868	1/2"X3/8"X1/2"	1.13	1.10
TR2-884	1/2"X1/2"X1/4"	1.14	.98
TR2-886	1/2"X1/2"X3/8"	1.20	1.08
TR2-8810	1/2"X1/2"X5/8"	1.28	1.40
TR2-10106	5/8"X5/8"X3/8"	1.38	1.16
TR2-10108	5/8"X5/8"X1/2"	1.38	1.28
TR2-10810	5/8"X1/2"X5/8"	1.44	1.40



RT2 FLARE UNION TEE

PART NUMBER	O.D. TUBE	A
RT2-4	1/4"	.88
RT2-6	3/8"	1.06
RT2-8	1/2"	1.22
RT2-10	5/8"	1.41




REF SAE 010401

REF SAE 010401

*Read dimensions 1 & 2 across run, 3 as branch

T3 MALE RUN TEE



PART NUMBER	O.D. TUBE	MPT	A	B
T3-3A	3/16"	1/8"	.80	.75
T3-4A	1/4"	1/8"	.80	.75
T3-4B	1/4"	1/4"	.88	.88
T3-4C	1/4"	3/8"	.88	1.10
T3-5A	5/16"	1/8"	.90	.78
T3-5B	5/16"	1/4"	.94	.96
T3-6A	3/8"	1/8"	1.00	.88
T3-6B	3/8"	1/4"	1.02	.90
T3-6C	3/8"	3/8"	1.02	1.10
T3-6D	3/8"	1/2"	1.12	1.22
T3-8C	1/2"	3/8"	1.16	1.10
T3-8D	1/2"	1/2"	1.20	1.20
T3-10D	5/8"	1/2"	1.32	1.32
T3-12D	3/4"	1/2"	1.58	1.58
T3-12E	3/4"	3/4"	1.43	1.43



REF SAE 010424



T4 FLARE STREET TEE

PART NUMBER	O.D. TUBE	FPT	A	B
T4-4A	1/4"	1/8"	.88	.80
T4-4B	1/4"	1/4"	.88	.80





U1 MALE FLARE CONNECTOR

PART NUMBER	O.D. TUBE	MPT	A	HEX
U1-2A	1/8"	1/8"	.92	7/16"
U1-3A	3/16"	1/8"	1.00	7/16"
U1-4A	1/4"	1/8"	1.06	7/16"
U1-4B	1/4"	1/4"	1.12	9/16"
U1-4C	1/4"	3/8"	1.31	11/16"
U1-4D	1/4"	1/2"	1.31	7/8"
U1-5A	5/16"	1/8"	1.31	1/2"
U1-5B	5/16"	1/4"	1.22	9/16"
U1-5C	5/16"	3/8"	1.31	11/16"
U1-6A	3/8"	1/8"	1.25	5/8"
U1-6B	3/8"	1/4"	1.31	5/8"
U1-6C	3/8"	3/8"	1.38	11/16"
U1-6D	3/8"	1/2"	1.44	7/8"
U1-6E	3/8"	3/4"	1.56	1-1/16"
U1-8B	1/2"	1/4"	1.50	3/4"
U1-8C	1/2"	3/8"	1.50	3/4"
U1-8D	1/2"	1/2"	1.56	7/8"
U1-8E	1/2"	3/4"	1.68	1-1/16"
U1-10B	5/8"	1/4"	1.95	7/8"
U1-10C	5/8"	3/8"	1.62	7/8"
U1-10D	5/8"	1/2"	1.75	7/8"
U1-10E	5/8"	3/4"	1.81	1-1/16"
U1-12D	3/4"	1/2"	1.97	1-1/16"
U1-12E	3/4"	3/4"	2.00	1-1/16"
U1-14E	7/8"	3/4"	2.27	1-3/16"



RU1 MALE FLARE CONNECTOR



PART NUMBER	O.D. TUBE	MPT	A	HEX
RU1-4A	1/4"	1/8"	1.06	7/16"
RU1-4B	1/4"	1/4"	1.25	9/16"
RU1-4C	1/4"	3/8"	1.31	11/16"
RU1-4D	1/4"	1/2"	1.56	7/8"
RU1-5A	5/16"	1/8"	1.16	1/2"
RU1-5B	5/16"	1/4"	1.34	9/16"
RU1-6A	3/8"	1/8"	1.25	5/8"
RU1-6B	3/8"	1/4"	1.44	5/8"
RU1-6C	3/8"	3/8"	1.44	11/16"
RU1-6D	3/8"	1/2"	1.69	7/8"
RU1-6E	3/8"	3/4"	1.81	1-1/16"
RU1-8B	1/2"	1/4"	1.62	3/4"
RU1-8C	1/2"	3/8"	1.62	3/4"
RU1-8D	1/2"	1/2"	1.88	7/8"
RU1-8E	1/2"	3/4"	1.94	1-1/16"
RU1-10C	5/8"	3/8"	1.81	7/8"
RU1-10D	5/8"	1/2"	2.00	7/8"
RU1-10E	5/8"	3/4"	2.06	1-1/16"



REF SAE 010102

U2 MALE FLARE UNION


PART NUMBER	O.D. TUBE	A	HEX
U2-2	1/8"	.91	7/16"
U2-3	3/16"	1.00	7/16"
U2-4	1/4"	1.19	7/16"
U2-5	5/16"	1.34	1/2"
U2-6	3/8"	1.50	5/8"
U2-8	1/2"	1.81	3/4"
U2-10	5/8"	2.06	3/4"
U2-12	3/4"	2.44	1-1/16"
U2-14	7/8"	2.72	1-3/16"



RU2 MALE FLARE UNION

PART NUMBER	O.D. TUBE	A	HEX
RU2-4	1/4"	1.19	7/16"
RU2-6	3/8"	1.50	5/8"
RU2-8	1/2"	1.81	3/4"
RU2-10	5/8"	2.12	7/8"
RU2-12	3/4"	2.44	1-1/16"

REF SAE 010101





UR3 REDUCER FEMALE TO MALE FLARE

PART NUMBER	O.D. TUBE F	O.D. TUBE M	A	HEX
UR3-46	1/4"	3/8"	1.12	5/8"
UR3-64	3/8"	1/4"	1.22	13/16"
UR3-68	3/8"	1/2"	1.41	13/16"
UR3-86	1/2"	3/8"	1.44	15/16"
UR3-810	1/2"	5/8"	1.62	15/16"
UR3-108	5/8"	1/2"	1.68	1-1/16"


*Use with B2 Series

(Copper Gasket)





UR2 UNION REDUCER

PART NUMBER	O.D. TUBE	A	HEX
UR2-64	3/8"X1/4"	1.38	5/8"
UR2-65	3/8"X5/16"	1.42	11/16"
UR2-84	1/2"X1/4"	1.50	3/4"
UR2-86	1/2"X3/8"	1.62	3/4"
UR2-106	5/8"X3/8"	1.81	7/8"
UR2-108	5/8"X1/2"	1.94	7/8"
UR2-128	3/4"X1/2"	2.19	1-1/16"
UR2-1210	3/4"X5/8"	2.19	1-1/16"




U3 ADAPTER TUBE TO FPT

PART NUMBER	O.D. TUBE	FPT	A	HEX
U3-3A	3/16"	1/8"	.97	9/16"
U3-4A	1/4"	1/8"	1.00	1/2"
U3-4B	1/4"	1/4"	1.06	5/8"
U3-4C	1/4"	3/8"	1.18	3/4"
U3-5A	5/16"	1/8"	1.06	9/16"
U3-5B	5/16"	1/4"	1.28	11/16"
U3-6A	3/8"	1/8"	1.09	5/8"
U3-6B	3/8"	1/4"	1.09	5/8"
U3-6C	3/8"	3/8"	1.22	13/16"
U3-6D	3/8"	1/2"	1.31	15/16"
U3-6E	3/8"	3/4"	1.31	1-1/8"
U3-8B	1/2"	1/4"	1.34	13/16"
U3-8C	1/2"	3/8"	1.34	13/16"
U3-8D	1/2"	1/2"	1.44	15/16"
U3-8E	1/2"	3/4"	1.41	1-1/8"
U3-10C	5/8"	3/8"	1.45	7/8"
U3-10D	5/8"	1/2"	1.50	15/16"
U3-10E	5/8"	3/4"	1.53	1-1/8"
U3-12D	3/4"	1/2"	1.75	1-1/8"
U3-12E	3/4"	3/4"	1.88	1-1/4"
U3-14E	7/8"	3/4"	1.94	1-15/16"



UR2 UNION REDUCER

PART NUMBER	O.D. TUBE	A	HEX
RUR2-64	3/8"X1/4"	1.38	5/8"
RUR2-65	3/8"X5/16"	1.69	3/4"
RUR2-106	5/8"X3/8"	1.89	7/8"
RUR2-108	5/8"X1/2"	2.00	7/8"





REF SAE 010101

RU3 FLARE TO FEMALE PIPE



PART NUMBER	O.D. TUBE	FPT	A	HEX
RU3-4A	1/4"	1/8"	1.03	9/16"
RU3-4B	1/4"	1/4"	1.25	11/16"
RU3-6B	3/8"	1/4"	1.31	13/16"
RU3-6C	3/8"	3/8"	1.38	13/16"
RU3-6D	3/8"	1/2"	1.62	1"
RU3-8C	1/2"	3/8"	1.50	13/16"
RU3-8D	1/2"	1/2"	1.75	1"
RU3-10D	5/8"	1/2"	1.81	1"
RU3-10E	5/8"	3/4"	1.91	1-1/4"

REF SAE 010103





US4 SWIVEL FLARE CONNECTOR

PART NUMBER	O.D. TUBE	A
US4-4	1/4"	1.50
US4-5	5/16"	1.52
US4-6	3/8"	1.55
US4-64	3/8"X1/4"	1.48
US4-8	1/2"	1.85
US4-86	1/2"X3/8"	1.73
US4-10	5/8"	2.15
US4-108	5/8"X1/2"	1.96
US4-12	3/4"	2.50




US3 FLARE TO SOLDER

PART NUMBER	O.D. TUBE	SOLDER	A	HEX
US3-44	1/4"	1/4"	1.00	7/16"
US3-46	1/4"	3/8"	1.00	1/2"
US3-66	3/8"	3/8"	1.25	5/8"
US3-88	1/2"	1/2"	1.50	3/4"
US3-1010	5/8"	5/8"	1.75	7/8"
US3-1214	3/4"	7/8"	1.97	1-1/16"



U4 FLARE CONNECTOR

PART NUMBER	O.D. TUBE	A	HEX
U4-4	1/4"	1.00	5/8"
U4-6	3/8"	1.25	13/16"
U4-8	1/2"	1.44	15/16"



REF SAE 010107


*Use with B2 Series

(Copper Gasket)





NYLON AIR BRAKE DOT FITTINGS

CONSTRUCTION	• CA360 Brass (Straights) • CA360 Brass (Shapes) 
APPLICATIONS	• Air Brake Systems 
RANGES	• Temperature Range: -40° to 200° F. • Pressure Range: Up to 150 PSI 



Assembly Instructions

1. Cut tubing squarely—using a tube cutter.
2. Make sure all fittings involved in the assembly are clean of burrs and debris.
3. Insert nylon air brake tubing firmly into the fitting until it bottoms out.
4. Tighten nut according to the chart listed below:

Tube Size	Turns Past Hand-Tight
3/16	2.5
1/4	3
3/8 + 1/2	4
5/8 + 3/4	3.5

Application Details:




Transportation Air Brake Systems, Air Suspensions, Cabin Controls:
Trucks, Trailers, RVs, Buses, Fire Trucks, & Rail.



NOTES


- Fittings meet SAE and DOT FMVSS 571.106
- Non-stock items and special parts are available on a quotation basis.
- Configurations and dimensions are subject to change without notice.

 **WARNING:** Products offered by Robo-Fit can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov

59A Tube Support Insert 	60NAB Sleeve 	61NAB Nut 	62NAB Union Tube, Both Ends 
62NABH Bulkhead Union 	64NAB Union Tee 	65NAB 90° Union Elbow 	66NAB Female Connector 
68NAB Male Connector 	68NABH Bulkhead Connector 	69NAB 90° Male Elbow 	70NAB 90° Female Elbow 
71NAB Male Run Tee 	72NAB Male Branch Tee 	79NAB 45° Male Elbow 	


59A TUBE SUPPORT INSERT

PART NUMBER	Tube O.D.	A
59A-4	1/4"	.51
59A-6	3/8"	.64
59A-8	1/2"	.81
59A-10	5/8"	.86
59A-12	3/4"	1.06



62NAB UNION TUBE, BOTH ENDS


PART NUMBER	Tube O.D.	A	HEX
62NAB-4	1/4"	1.45	7/16"
62NAB-6	3/8"	1.80	9/16"
62NAB-8	1/2"	2.03	11/16"
62NAB-10	5/8"	2.29	13/16"
62NAB-12	3/4"	2.62	1"



REF SAE 100101BA

60NAB SLEEVE


PART NUMBER	Tube O.D.	A
60NAB-4	1/4"	.31
60NAB-6	3/8"	.39
60NAB-8	1/2"	.43
60NAB-10	5/8"	.44
60NAB-12	3/4"	.54



REF SAE 100115BA


62NABH BULKHEAD UNION, BOTH ENDS

PART NUMBER	Tube O.D.	A	Hex
62NABH-6	3/8"	2.90	9/16"
62NABH-8	1/2"	3.20	11/16"



61NAB NUT


PART NUMBER	Tube O.D.	A	HEX
61NAB-4	1/4"	.45	9/16"
61NAB-6	3/8"	.56	5/8"
61NAB-8	1/2"	.66	13/16"
61NAB-10	5/8"	.74	15/16"
61NAB-12	3/4"	.81	1-1/8"



REF SAE 100110BA

64NAB UNION TEE


PART NUMBER	Tube O.D.	A
64NAB-4	1/4"	.95
64NAB-6	3/8"	1.24
64NAB-8	1/2"	1.45
64NAB-10	5/8"	1.58



REF SAE 100401BA

65NAB 90° UNION ELBOW


PART NUMBER	Tube O.D.	A
65NAB-4	1/4"	1.00
65NAB-6	3/8"	1.14
65NAB-8	1/2"	1.32
65NAB-10	5/8"	1.60



REF SAE 100201BA

66NAB FEMALE CONNECTOR


PART NUMBER	Tube O.D.	FPT	A	HEX
66NAB-4A	1/4"	1/8"	1.18	9/16"
66NAB-4B	1/4"	1/4"	1.40	11/16"
66NAB-6A	3/8"	1/8"	1.50	9/16"
66NAB-6B	3/8"	1/4"	1.60	11/16"
66NAB-6C	3/8"	3/8"	1.71	7/8"
66NAB-8C	1/2"	3/8"	1.80	7/8"
66NAB-8D	1/2"	1/2"	1.89	1-1/16"



REF SAE 100103BA

68NAB MALE CONNECTOR



PART NUMBER	Tube O.D.	MPT	A	HEX
68NAB-4A	1/4"	1/8"	1.21	7/16"
68NAB-4B	1/4"	1/4"	1.42	9/16"
68NAB-4C	1/4"	3/8"	1.46	11/16"
68NAB-6A	3/8"	1/8"	1.37	9/16"
68NAB-6B	3/8"	1/4"	1.58	9/16"
68NAB-6C	3/8"	3/8"	1.58	11/16"
68NAB-6D	3/8"	1/2"	1.80	7/8"
68NAB-8B	1/2"	1/4"	1.71	11/16"
68NAB-8C	1/2"	3/8"	1.71	11/16"
68NAB-8D	1/2"	1/2"	1.90	7/8"
68NAB-10C	5/8"	3/8"	1.84	13/16"
68NAB-10D	5/8"	1/2"	2.03	7/8"
68NAB-12D	3/4"	1/2"	2.21	1"
68NAB-12E	3/4"	3/4"	2.22	1-1/16"



REF SAE 100102BA

69NAB 90° MALE ELBOW


PART NUMBER	Tube O.D.	MPT	A	B
69NAB-4A	1/4"	1/8"	.95	.66
69NAB-4B	1/4"	1/4"	1.00	.87
69NAB-4C	1/4"	3/8"	1.16	.86
69NAB-6A	3/8"	1/8"	1.19	.75
69NAB-6B	3/8"	1/4"	1.25	.92
69NAB-6C	3/8"	3/8"	1.30	.91
69NAB-6D	3/8"	1/2"	1.40	1.10
69NAB-8B	1/2"	1/4"	1.38	.99
69NAB-8C	1/2"	3/8"	1.44	.99
69NAB-8D	1/2"	1/2"	1.55	1.18
69NAB-10C	5/8"	3/8"	1.49	1.05
69NAB-10D	5/8"	1/2"	1.58	1.24
69NAB-10E	5/8"	3/4"	1.76	1.32
69NAB-12D	3/4"	1/2"	1.70	1.33
69NAB-12E	3/4"	3/4"	1.77	1.32




REF SAE 100202BA

68NABH BULKHEAD CONNECTOR

PART NUMBER	Tube O.D.	FPT	A	HEX
68NABH-6C	3/8"	3/8"	1.31	1-1/16"
68NABH-8C	1/2"	3/8"	1.93	1-1/16"




7/8"-20 UNEF-2A



70NAB 90° FEMALE ELBOW

PART NUMBER	Tube O.D.	FPT	A	B
70NAB-4A	1/4"	1/8"	1.02	.52
70NAB-4B	1/4"	1/4"	1.11	.71
70NAB-6A	3/8"	1/8"	1.29	.59
70NAB-6B	3/8"	1/4"	1.35	.77
70NAB-6C	3/8"	3/8"	1.39	.77
70NAB-8C	1/2"	3/8"	1.55	.82
70NAB-8D	1/2"	1/2"	1.65	1.01
70NAB-10D	5/8"	1/2"	1.70	1.07


REF SAE 100203BA



72NAB MALE BRANCH TEE

PART NUMBER	Tube O.D.	MPT	A	B
72NAB-4A	1/4"	1/8"	.66	1.80
72NAB-4B	1/4"	1/4"	.87	2.00
72NAB-6A	3/8"	1/8"	.75	2.36
72NAB-6B	3/8"	1/4"	.92	2.50
72NAB-6C	3/8"	3/8"	.91	2.60
72NAB-8B	1/2"	1/4"	.99	2.82
72NAB-8C	1/2"	3/8"	.99	2.90
72NAB-8D	1/2"	1/2"	1.18	3.10
72NAB-10D	5/8"	1/2"	1.24	3.20


REF SAE 100425BA



71NAB MALE RUN TEE


PART NUMBER	Tube O.D.	MPT	A	B
71NAB-4A	1/4"	1/8"	.95	1.61
71NAB-4B	1/4"	1/4"	1.00	1.87
71NAB-6B	3/8"	1/4"	1.25	2.17
71NAB-6C	3/8"	3/8"	1.30	2.21
71NAB-8C	1/2"	3/8"	1.45	2.44
71NAB-8D	1/2"	1/2"	1.55	2.73
71NAB-10D	5/8"	1/2"	1.60	2.84

REF SAE 100424BA



79NAB 45° MALE ELBOW

PART NUMBER	Tube O.D.	MPT	A	B
79NAB-4A	1/4"	1/8"	.81	.63
79NAB-4B	1/4"	1/4"	.93	.85
79NAB-6A	3/8"	1/8"	1.17	.68
79NAB-6B	3/8"	1/4"	1.17	.85
79NAB-6C	3/8"	3/8"	1.21	.94
79NAB-6D	3/8"	1/2"	1.24	1.16
79NAB-8B	1/2"	1/4"	1.36	.94
79NAB-8C	1/2"	3/8"	1.36	.94
79NAB-8D	1/2"	1/2"	1.39	1.16
79NAB-10C	5/8"	3/8"	1.43	.98
79NAB-10D	5/8"	1/2"	1.42	1.16
79NAB-12D	3/4"	1/2"	1.61	1.18





BRASS PUSH-IN DOT FITTINGS

CONSTRUCTION	• CA360/CA3604 Brass (Straights) • CA377/CA3604 Brass (Shapes) • "O" Ring: Buna N (Nitrile)	
APPLICATIONS	• Air Brake Systems	
RANGES	• Temperature Range: -40° to 200° F. • Pressure Range: Up to 200 PSI	



- To Connect Fitting & Tubing:**
1. Cut the air brake tubing squarely.
 2. Make sure mating ports are free of any debris.
 3. Insert the tubing past the O-Ring until the tubing bottoms out against the tube stop.
 4. Check your connection by pulling on the tubing to ensure tubing is fully inserted.

- To Disconnect Fitting & Tubing:**
1. Press and hold the collet against the fitting body.
 2. Pull the tubing out of fitting.

Application Details:









Transportation Air Brake Systems, Air Suspensions, Cabin Controls:

Trucks, Trailers, RVs, Buses, Fire Trucks, & Rail.



- NOTES**
- Fittings meet SAE and DOT FMVSS 571.106
 - Non-stock items and special parts are available on a quotation basis.
 - Configurations and dimensions are subject to change without notice.

 **WARNING:** Products offered by Robo-Fit can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov

259PPDOT Tube Plug 	262PPDOT Union 	262PPBHDOT Bulkhead Union 	264PPDOT Union Tee 
265PPDOT 90° Union Elbow 	266PPDOT Female Connector 	268PPDOT Male Connector 	2688PPDOT Plug In Adapter 
269PPDOT 90° Male Elbow 	269PPSDOT 90° Male Swivel Elbow 	270PPDOT 90° Female Elbow 	270PPSDOT 90° Female Swivel Elbow 
271PPDOT Male Run Tee 	271PPSDOT Male Swivel Run Tee 	272PPDOT Male Branch Tee 	272PPSDOT Male Swivel Branch Tee 
277PPDOT Female Branch Tee 	277PPSDOT Female Swivel Branch Tee 	279PPDOT 45° Male Elbow 	279PPSDOT 45° Male Swivel Elbow 
283PPDOT Gladhand Bulkhead 	286PPDOT Female Bulkhead 		


259PPDOT NYLON PLUG

PART NUMBER	PLUG TUBE O.D.
259PPDOT-2.5	5/32"
259PPDOT-4	1/4"
259PPDOT-6	3/8"
259PPDOT-8	1/2"
259PPDOT-10	5/8"
259PPDOT-12	3/4"





262PPDOT UNION CONNECTOR

PART NUMBER	Tube O.D.	A	B
262PPDOT-2.5	5/32"	1.38	3/8"
262PPDOT-3	3/16"	1.60	7/16"
262PPDOT-4	1/4"	1.82	7/16"
262PPDOT-2.5	5/16"	1.89	19/32"
262PPDOT-6	3/8"	1.82	21/32"
262PPDOT-8	1/2"	2.02	25/32"
262PPDOT-10	5/8"	2.04	.91
262PPDOT-12	3/4"	2.20	1.06




262PPBHDOT BULKHEAD UNION

PART NUMBER	Tube O.D.	A	C	D
262PPBHDOT-4	1/4"	1.90	3/8	1/2-20
262PPBHDOT-6	3/8"	1.85	7/16	3/4-16
262PPBHDOT-8	1/2"	2.05	7/16	15/16-16
262PPBHDOT-10	5/8"	2.05	19/32	1/4




264PPDOT UNION TEE

PART NUMBER	Tube O.D.	A	B	FLATS
264PPDOT-4	1/4"	.94	1.17	3/8"
264PPDOT-6	3/8"	1.08	1.41	1/2"
264PPDOT-8	1/2"	1.26	1.65	5/8"
264PPDOT-10	5/8"	1.32	1.77	11/16"
264PPDOT-12	3/4"	1.44	1.99	15/16"




265PPDOT 90° UNION ELBOW

PART NUMBER	Tube O.D.	A	B	FLATS
265PPDOT-4	1/4"	.94	1.17	3/8"
265PPDOT-6	3/8"	1.08	1.41	1/2"
265PPDOT-8	1/2"	1.26	1.65	5/8"




266PPDOT FEMALE CONNECTOR

PART NUMBER	Tube O.D.	FPT	A	HEX
266PPDOT-4A	1/4"	1/8"	1.33	9/16"
266PPDOT-4B	1/4"	1/4"	1.55	3/4"
266PPDOT-6A	3/8"	1/8"	1.33	11/16"
266PPDOT-6B	3/8"	1/4"	1.52	3/4"
266PPDOT-6C	3/8"	3/8"	1.56	7/8"
266PPDOT-8C	1/2"	3/8"	1.59	7/8"
266PPDOT-8D	1/2"	1/2"	1.85	1-1/8"




268PPDOT MALE CONNECTOR

PART NUMBER	Tube O.D.	MPT	A	HEX
268PPDOT-2.5X1	5/32"	1/16"	.78	3/8"
268PPDOT-2.5A	5/32"	1/8"	.79	7/16"
268PPDOT-2.5B	5/32"	1/4"	.95	9/16"
268PPDOT-3X0	3/16"	10/32"	.89	3/8"
268PPDOT-3X1	3/16"	1/16"	1.02	3/8"
268PPDOT-3A	3/16"	1/8"	1.02	7/16"
268PPDOT-3B	3/16"	1/4"	1.02	9/16"
268PPDOT-4X1	1/4"	1/16"	1.17	7/16"
268PPDOT-4A	1/4"	1/8"	.98	7/16"
268PPDOT-4B	1/4"	1/4"	.90	9/16"
268PPDOT-4C	1/4"	3/8"	.87	11/16"
268PPDOT-6A	3/8"	1/8"	1.17	11/16"
268PPDOT-6B	3/8"	1/4"	1.15	11/16"
268PPDOT-6C	3/8"	3/8"	1.12	11/16"
268PPDOT-6D	3/8"	1/2"	1.03	7/8"
268PPDOT-8B	1/2"	1/4"	1.46	13/16"
268PPDOT-8C	1/2"	3/8"	1.28	13/16"
268PPDOT-8D	1/2"	1/2"	1.23	7/8"
268PPDOT-8E	1/2"	3/4"	1.29	1-1/16"
268PPDOT-10C	5/8"	3/8"	1.44	15/16"
268PPDOT-10D	5/8"	1/2"	1.59	15/16"
268PPDOT-10E	5/8"	3/4"	1.13	1-1/16"
268PPDOT-12D	3/4"	1/2"	1.65	1-1/16"
268PPDOT-12E	3/4"	3/4"	1.38	1-1/16"




269PPDOT 90° MALE ELBOW

PART NUMBER	Tube O.D.	MPT	A	B	C
269PPDOT-2.5X1	5/32"	1/16"	.78	.65	5/16"
269PPDOT-2.5A	5/32"	1/8"	.78	.69	5/16"
269PPDOT-3A	3/16"	1/8"	.88	.75	3/8"
269PPDOT-4A	1/4"	1/8"	1.01	.79	3/8"
269PPDOT-4B	1/4"	1/4"	1.05	.84	3/8"
269PPDOT-4C	1/4"	3/8"	1.10	.98	1/2"
269PPDOT-6A	3/8"	1/8"	1.00	.80	1/2"
269PPDOT-6B	3/8"	1/4"	1.10	.98	1/2"
269PPDOT-6C	3/8"	3/8"	1.08	.98	1/2"
269PPDOT-6D	3/8"	1/2"	1.14	1.20	5/8"
269PPDOT-8B	1/2"	1/4"	1.26	1.05	5/8"
269PPDOT-8C	1/2"	3/8"	1.26	1.05	5/8"
269PPDOT-8D	1/2"	1/2"	1.25	1.26	5/8"
269PPDOT-10C	5/8"	3/8"	1.25	1.26	5/8"
269PPDOT-10D	5/8"	1/2"	1.34	1.29	11/16"
269PPDOT-12D	3/4"	1/2"	1.32	1.36	15/16"
269PPDOT-12E	3/4"	3/4"	1.32	1.36	15/16"




2688PPDOT PRESS-IN CARTRIDGE

PART NUMBER	Tube O.D.	A	B	C
2688PPDOT-2.5	5/32"	.59	.69	.32
2688PPDOT-3	3/16"	.68	.78	.41
2688PPDOT-4	1/4"	.76	.86	.41
2688PPDOT-6	3/8"	.82	.92	.64
2688PPDOT-8	1/2"	.92	1.02	.77




269PPSDOT 90° MALE SWIVEL ELBOW

PART NUMBER	Tube O.D.	MPT	A	B	HEX
269PPSDOT-2.5A	5/32"	1/8"	.79	.88	7/16"
269PPSDOT-2.5B	5/32"	1/4"	.79	1.08	9/16"
269PPSDOT-3A	3/16"	1/8"	.88	.92	7/16"
269PPSDOT-4A	1/4"	1/8"	.94	1.09	9/16"
269PPSDOT-4B	1/4"	1/4"	.99	1.09	9/16"
269PPSDOT-4C	1/4"	3/8"	1.02	1.13	11/16"
269PPSDOT-6A	3/8"	1/8"	1.05	1.06	7/16"
269PPSDOT-6B	3/8"	1/4"	1.08	1.14	9/16"
269PPSDOT-6C	3/8"	3/8"	1.10	1.23	11/16"
269PPSDOT-6D	3/8"	1/2"	1.10	1.53	7/8"
269PPSDOT-8B	1/2"	1/4"	1.26	1.26	9/16"
269PPSDOT-8C	1/2"	3/8"	1.26	1.31	11/16"
269PPSDOT-8D	1/2"	1/2"	1.25	1.61	7/8"
269PPSDOT-10C	5/8"	3/8"	1.54	1.41	11/16"
269PPSDOT-10D	5/8"	1/2"	1.54	1.71	7/8"
269PPSDOT-12D	3/4"	1/2"	1.40	2.04	1-1/16"
269PPSDOT-12E	3/4"	3/4"	1.40	1.60	1-1/16"




270PPDOT 90° FEMALE ELBOW

PART NUMBER	Tube O.D.	FPT	A	B	C
270PPDOT-4A	1/4"	1/8"	1.02	.83	1.06
270PPDOT-4B	1/4"	1/4"	1.13	1.03	1.31
270PPDOT-4C	1/4"	3/8"	1.27	.99	1.35
270PPDOT-6B	3/8"	1/4"	1.08	.98	1.31
270PPDOT-6C	3/8"	3/8"	1.08	1.05	1.41
269PPDOT-8D	1/2"	1/2"	1.37	1.31	1.70




271PPSDOT MALE SWIVEL RUN TEE

PART NUMBER	Tube O.D.	MPT	A	B	C
271PPSDOT-4A	1/4"	1/8"	2.03	1.02	3/8"
271PPSDOT-4B	1/4"	1/4"	2.10	1.02	7/16"
271PPSDOT-6B	3/8"	1/4"	2.19	1.04	1/2"
271PPSDOT-6C	3/8"	3/8"	2.23	1.06	1/2"
271PPSDOT-8C	1/2"	3/8"	2.52	1.24	5/8"
271PPSDOT-8D	1/2"	1/2"	2.82	1.24	5/8"




270PPSDOT 90° FEMALE SWIVEL ELBOW

PART NUMBER	Tube O.D.	FPT	A	B	C
270PPSDOT-4A	1/4"	1/8"	.94	1.09	9/16"
270PPSDOT-4B	1/4"	1/4"	.97	1.25	3/4"
270PPSDOT-6B	3/8"	1/4"	1.10	1.48	3/4"




272PPDOT MALE BRANCH TEE

PART NUMBER	Tube O.D.	MPT	A	B
272PPDOT-4A	1/4"	1/8"	1.02	.75
272PPDOT-4B	1/4"	1/4"	1.02	.92
272PPDOT-6A	3/8"	1/8"	1.08	.79
272PPDOT-6B	3/8"	1/4"	1.08	.99
272PPDOT-6C	3/8"	3/8"	1.09	.99
272PPDOT-8B	1/2"	1/4"	1.26	1.07
272PPDOT-8C	1/2"	3/8"	1.26	1.07




271PPDOT MALE RUN TEE

PART NUMBER	Tube O.D.	MPT	A	B	C
271PPDOT-4A	1/4"	1/8"	1.02	.75	1.02
271PPDOT-4B	1/4"	1/4"	1.02	.92	1.02
271PPDOT-4C	1/4"	3/8"	1.08	.98	1.08
271PPDOT-6B	3/8"	1/4"	1.08	.98	1.08
271PPDOT-6C	3/8"	3/8"	1.08	.98	1.08
271PPDOT-8C	1/2"	3/8"	1.26	1.05	1.26




272PPSDOT MALE SWIVEL BRANCH TEE

PART NUMBER	Tube O.D.	MPT	A	B	C
272PPSDOT-4A	1/4"	1/8"	1.02	1.04	7/16"
272PPSDOT-4B	1/4"	1/4"	1.01	1.04	9/16"
272PPSDOT-6A	3/8"	1/8"	1.08	1.07	7/16"
272PPSDOT-6B	3/8"	1/4"	1.06	1.17	9/16"
272PPSDOT-6C	3/8"	3/8"	1.08	1.21	11/16"
272PPSDOT-6D	3/8"	1/2"	1.08	1.40	7/8"
272PPSDOT-8B	1/2"	1/4"	1.26	1.28	9/16"
272PPSDOT-8C	1/2"	3/8"	1.26	1.31	11/16"
272PPSDOT-8D	1/2"	1/2"	1.26	1.61	7/8"
272PPSDOT-10D	5/8"	1/2"	1.32	1.74	7/8"




277PPDOT FEMALE BRANCH TEE

PART NUMBER	Tube O.D.	FPT	A	B	C
277PPDOT-4A	1/4"	1/8"	1.02	.82	1/2"
277PPDOT-4B	1/4"	1/4"	1.08	.97	1/2"
277PPDOT-6B	3/8"	1/4"	1.09	.98	1/2"
277PPDOT-6C	3/8"	3/8"	1.40	1.30	11/16"
277PPDOT-8B	1/2"	1/4"	1.26	1.16	5/8"




277PPSDOT FEMALE SWIVEL BRANCH TEE

PART NUMBER	Tube O.D.	FPT	A	B	C
277PPSDOT-4A	1/4"	1/8"	1.02	1.13	9/16"
277PPSDOT-4B	1/4"	1/4"	1.02	1.29	3/4"
277PPSDOT-6A	3/8"	1/8"	1.08	1.18	9/16"
277PPSDOT-6C	3/8"	3/8"	1.08	1.16	3/4"




279PPDOT 45° MALE ELBOW

PART NUMBER	Tube O.D.	MPT	A	B
279PPDOT-4A	1/4"	1/8"	.75	.99
279PPDOT-4B	1/4"	1/4"	.89	.99
279PPDOT-6A	3/8"	1/8"	.75	.99
279PPDOT-6B	3/8"	1/4"	.95	1.08
279PPDOT-6C	3/8"	3/8"	.97	1.08
279PPDOT-6D	3/8"	1/2"	1.13	1.15
279PPDOT-8B	1/2"	1/4"	1.00	1.20
279PPDOT-8C	1/2"	3/8"	1.05	1.20
279PPDOT-8D	1/2"	1/2"	1.20	1.20
279PPDOT-10C	5/8"	3/8"	1.17	1.22
279PPDOT-10D	5/8"	1/2"	1.31	1.22
279PPDOT-12D	3/4"	1/2"	1.36	1.18
279PPDOT-12E	3/4"	3/4"	1.36	1.18





279PPSDOT 45° MALE SWIVEL ELBOW

PART NUMBER	Tube O.D.	MPT	A	B	C
279PPSDOT-4A	1/4"	1/8"	.98	.99	7/16"
279PPSDOT-4B	1/4"	1/4"	1.06	.99	7/16"
279PPSDOT-6A	3/8"	1/8"	1.08	1.06	7/16"
279PPSDOT-6B	3/8"	1/4"	1.13	1.06	9/16"
279PPSDOT-6C	3/8"	3/8"	1.23	1.08	11/16"
279PPSDOT-6D	3/8"	1/2"	1.46	1.22	7/8"
279PPSDOT-8B	1/2"	1/4"	1.22	1.22	9/16"
279PPSDOT-8C	1/2"	3/8"	1.32	1.20	11/16"
279PPSDOT-8D	1/2"	1/2"	1.61	1.20	7/8"
279PPSDOT-10C	5/8"	3/8"	1.38	1.33	11/16"
279PPSDOT-10D	5/8"	1/2"	1.68	1.39	7/8"
279PPSDOT-12E	3/4"	3/4"	2.28	1.40	1-1/16"





283PPDOT GLADHAND BULKHEAD


PART NUMBER	Tube O.D.	MPT	A	B	C	D
283PPDOT-6D	3/8"	1/2"	1.99	1-3/8	1-1/4	1-14
283PPDOT-8D	1/2"	1/2"	1.99	1-3/8	1-1/4	1-14
283PPDOT-10D	5/8"	1/2"	2.33	1-3/8	1-1/4	1-14



286PPDOT FEMALE BULKHEAD UNION

PART NUMBER	Tube O.D.	FPT	A	B	C	D	E
286PPDOT-4A	1/4"	1/8"	1.32	.64	1/2-20	11/16	11/16
286PPDOT-4B	1/4"	1/4"	1.56	.64	1/2-20	11/16	11/16
286PPDOT-6B	3/8"	1/4"	1.87	1.00	3/4-16	15/16	15/16
286PPDOT-6C	3/8"	3/8"	1.87	1.00	3/4-16	15/16	15/16
286PPDOT-8C	1/2"	3/8"	2.04	1.00	15/16-16	1-1/8	1 3/8






COMPOSITE DOT FITTINGS

CONSTRUCTION

Polybutylene Terephthalate (PBT)
Thermoplastic Engineered Polymer

- Brass



APPLICATIONS


- Air Brake Systems



RANGES

- Temperature Range: -40° to 140° F

- Pressure Range: Up to 145 PSI



To Connect Fitting & Tubing:

1. Cut the air brake tubing squarely.
2. Make sure mating ports are free of any debris.
3. Insert the tubing past the O-Ring until the tubing bottoms out against the tube stop.
4. Check your connection by pulling on the tubing to ensure tubing is fully inserted.

To Disconnect Fitting & Tubing:

1. Press and hold the collet against the fitting body.
2. Pull the tubing out of fitting.

Application Details:

Transportation Air Brake Systems, Air Suspensions, Cabin Controls:


Trucks, Trailers, RVs, Buses, Fire Trucks, & Rail.



NOTES

- Fittings meet SAE and DOT FMVSS 571.106
- Non-stock items and special parts are available on a quotation basis.
- Configurations and dimensions are subject to change without notice.

 **WARNING:** Products offered by Robo-Fit can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov

C259PPDOT Tube Plug 	C262PPDOT Union 	C262PPBHDOT Bulkhead Union 	C264PPDOT Union Tee 
C265PPDOT 90° Union 	C266PPDOT Female Connector 	C268PPDOT Male Connector 	C2688PPDOT Plug In Adapter 
269PPSDOT 90° Male Swivel Elbow 	270PPSDOT Female Swivel Elbow 	271PPSDOT Swivel Run Tee 	272PPSDOT Swivel Branch Tee 
277PPSDOT FM Swivel Branch Tee 	279PPSDOT 45° Swivel Elbow 	286PPDOT Female Bulkhead 	


C259PPDOT NYLON PLUG

PART NUMBER	A
C259PPDOT-2.5	5/32"
C259PPDOT-4	1/4"
C259PPDOT-6	3/8"
C259PPDOT-8	1/2"
C259PPDOT-10	5/8"
C259PPDOT-12	3/4"




C264PPDOT UNION TEE

PART NUMBER	Tube O.D.	A	B
C264PPDOT-2.5	5/32"	18.3	18.3
C264PPDOT-4	1/4"	20.6	20.6
C264PPDOT-6	3/8"	26.2	26.2
C264PPDOT-664	3/8" x 1/4"	19.3	25.0
C264PPDOT-8	1/2"	28.8	28.8
C264PPDOT-10	5/8"	33.4	33.4




C262PPDOT UNION CONNECTOR

PART NUMBER	Tube O.D.	A
C262PPDOT-2.5	5/32"	32.6
C262PPDOT-4	1/4"	34.6
C262PPDOT-6	3/8"	42.6
C262PPDOT-8	1/2"	44.6
C262PPDOT-10	5/8"	53.4
C262PPDOT-12	3/4"	68.2




C265PPDOT 90° UNION ELBOW

PART NUMBER	Tube O.D.	A
C265PPDOT-2.5	5/32"	18.3
C265PPDOT-4	1/4"	20.6
C265PPDOT-6	3/8"	26.1
C265PPDOT-8	1/2"	28.9





C262PPBHDOT BULKHEAD UNION

PART NUMBER	Tube O.D.	A	HEX	Thread
C262PPBHDOT-2.5	5/32"	32.1	17.46	1/2-20
C262PPBHDOT-4	1/4"	34.1	17.46	9/16-18
C262PPBHDOT-6	3/8"	42.1	25.40	7/8-14
C262PPBHDOT-8	1/2"	44.1	28.57	1-12
C262PPBHDOT-10	5/8"	50.0	33.33	1 1/8-12




C266PPDOT FEMALE CONNECTOR

PART NUMBER	Tube O.D.	FPT	A	Hex
C266PPDOT-2.5A	5/32"	1/8"	27.0	14.29
C266PPDOT-2.5B	5/32"	1/4"	30.7	17.46
C266PPDOT-4A	1/4"	1/8"	27.5	14.29
C266PPDOT-4B	1/4"	1/4"	31.2	17.46
C266PPDOT-4C	1/4"	3/8"	33.3	22.23
C266PPDOT-6A	3/8"	1/8"	30.8	17.46
C266PPDOT-6B	3/8"	1/4"	34.5	17.46
C266PPDOT-6C	3/8"	3/8"	36.6	22.23
C266PPDOT-6D	3/8"	1/2"	40.6	23.81
C266PPDOT-8A	1/2"	1/8"	31.4	22.23
C266PPDOT-8B	1/2"	1/4"	35.4	22.23
C266PPDOT-8C	1/2"	3/8"	36.4	22.23
C266PPDOT-8D	1/2"	1/2"	40.8	23.80
C266PPDOT-10D	5/8"	1/2"	42.9	25.40




C268PPDOT MALE CONNECTOR

PART NUMBER	Tube O.D.	MPT	A	HEX
C268PPDOT-2.50	5/32"	1/16"	21.7	11.11
C268PPDOT-2.5A	5/32"	1/8"	21.7	11.11
C268PPDOT-4A	1/4"	1/8"	22.2	12.70
C268PPDOT-4B	1/4"	1/4"	22.7	14.29
C268PPDOT-4C	1/4"	3/8"	21.7	17.46
C268PPDOT-4D	1/4"	1/2"	26.0	22.23
C268PPDOT-6A	3/8"	1/8"	30.7	17.46
C268PPDOT-6B	3/8"	1/4"	33.2	17.46
C268PPDOT-6C	3/8"	3/8"	28.7	17.46
C268PPDOT-6D	3/8"	1/2"	26.2	22.23
C268PPDOT-8B	1/2"	1/4"	34.2	22.23
C268PPDOT-8C	1/2"	3/8"	32.7	22.23
C268PPDOT-8D	1/2"	1/2"	29.7	22.23
C268PPDOT-10C	5/8"	3/8"	38.6	25.40
C268PPDOT-10D	5/8"	1/2"	37.9	25.40
C268PPDOT-12C	3/4"	3/8"	47.5	30.0
C268PPDOT-12D	3/4"	1/2"	50.5	30.0
C268PPDOT-12E	3/4"	3/4"	52.5	30.0




269PPSDOT 90° MALE ELBOW

PART NUMBER	Tube O.D.	MPT	A	B
C269PPSDOT-2.5A	5/32"	1/8"	20.6	23.4
C269PPSDOT-2.5B	5/32"	1/4"	20.6	27.4
C269PPSDOT-4A	1/4"	1/8"	20.6	23.4
C269PPSDOT-4B	1/4"	1/4"	20.6	27.4
C269PPSDOT-4C	1/4"	3/8"	20.6	29.4
C269PPSDOT-4D	1/4"	1/2"	20.6	33.4
C269PPSDOT-6A	3/8"	1/8"	26.2	26.6
C269PPSDOT-6B	3/8"	1/4"	26.2	29.6
C269PPSDOT-6C	3/8"	3/8"	26.2	31.6
C269PPSDOT-6D	3/8"	1/2"	26.2	36.5
C269PPSDOT-8B	1/2"	1/4"	28.8	31.5
C269PPSDOT-8C	1/2"	3/8"	28.8	33.5
C269PPSDOT-8D	1/2"	1/2"	28.8	37.5
C269PPSDOT-8E	1/2"	3/4"	29.0	40.7
C269PPSDOT-10C	5/8"	3/8"	33.4	37.8
C269PPSDOT-10D	5/8"	1/2"	33.4	40.8
C269PPSDOT-10E	5/8"	3/4"	33.4	44.1
C269PPSDOT-12D	3/4"	1/2"	44.1	45.5
C269PPSDOT-12E	3/4"	3/4"	44.1	48.7




C2688PPDOT PLUG IN

PART NUMBER	Tube O.D.	Cavity	A
C2688PPDOT-4B	1/4"	1/4" SAE	17.9
C2688PPDOT-4D	1/4"	1/2" SAE	17.8
C2688PPDOT-6B	3/8"	1/4" SAE	29.0
C2688PPDOT-6C	3/8"	3/8" SAE	21.5
C2688PPDOT-6D	3/8"	1/2" SAE	21.2
C2688PPDOT-8C	1/2"	3/8" SAE	31.9
C2688PPDOT-8D	1/2"	1/2" SAE	22.4
C2688PPDOT-10D	5/8"	1/2" SAE	35.0




270PPSDOT 90° FEMALE SWIVEL ELBOW

PART NUMBER	Tube O.D.	MPT	A	B
C270PPSDOT-2.5A	5/32"	1/8"	20.6	22.0
C270PPSDOT-2.5B	5/32"	1/4"	20.6	25.5
C270PPSDOT-4A	1/4"	1/8"	20.6	22.0
C270PPSDOT-4B	1/4"	1/4"	20.6	25.5
C270PPSDOT-4C	1/4"	3/8"	20.6	26.0
C270PPSDOT-6A	3/8"	1/8"	26.2	18.8
C270PPSDOT-6B	3/8"	1/4"	26.2	27.7
C270PPSDOT-6C	3/8"	3/8"	26.2	28.2
C270PPSDOT-6D	3/8"	1/2"	26.2	32.2
C270PPSDOT-8B	1/2"	1/4"	28.8	29.6
C270PPSDOT-8C	1/2"	3/8"	28.8	30.1
C270PPSDOT-8D	1/2"	1/2"	28.8	34.1
C270PPSDOT-10D	5/8"	1/2"	33.5	37.5




C271PPSDOT MALE SWIVEL RUN TEE

PART NUMBER	Tube O.D.	MPT	A	B	HEX
C271PPSDOT-2.5X	5/32"	1/16"	20.6	44	14.29
C271PPSDOT-2.5A	5/32"	1/8"	20.6	44	14.29
C271PPSDOT-2.5B	5/32"	1/4"	20.6	48	14.29
C271PPSDOT-464	1/4"x3/8"	3/8"	26.2	55.8	19.00
C271PPSDOT-4A	1/4"	1/8"	20.6	44	14.29
C271PPSDOT-4B	1/4"	1/4"	20.6	48	14.29
C271PPSDOT-4C	1/4"	3/8"	20.6	50	17.46
C271PPSDOT-644	3/8"	1/4"	25.7	55.3	19.00
C271PPSDOT-664	3/8"x1/4"	3/8"	25.7	57.7	19.00
C271PPSDOT-6B	3/8"	1/4"	26.2	55.8	19.00
C271PPSDOT-6C	3/8"	3/8"	26.2	57.8	19.00
C271PPSDOT-6D	3/8"	1/2"	26.2	61.8	22.23
C271PPSDOT-866	1/2"x3/8"	3/8"	27.1	58.7	23.80
C271PPSDOT-886	1/2"x3/8"	1/2"	27.1	49.1	22.23
C271PPSDOT-884	1/2"x1/4"	1/2"	26.6	62.2	23.80
C271PPSDOT-8B	1/2"	1/4"	28.8	60.3	19.00
C271PPSDOT-8C	1/2"	3/8"	28.8	62.3	19.00
C271PPSDOT-8D	1/2"	1/2"	28.8	66.3	22.23
C271PPSDOT-10D	5/8"	1/2"	33.5	74.5	23.80




C277PPSDOT FEMALE SWIVEL BRANCH TEE

PART NUMBER	Tube O.D.	FPT	A	B	HEX
C277PPSDOT-4A	1/4"	1/8"	22.0	20.6	14.29
C277PPSDOT-4B	1/4"	1/4"	25.5	20.6	17.46
C277PPSDOT-6A	3/8"	1/8"	19.0	26.0	17.46
C277PPSDOT-6B	3/8"	1/4"	27.7	26.2	17.46
C277PPSDOT-8C	1/2"	3/8"	30.1	28.8	22.23
C277PPSDOT-10B	5/8"	1/4"	25.8	33.4	23.80




C279PPSDOT 45° MALE ELBOW

PART NUMBER	Tube O.D.	MPT	A	B	HEX
C279PPSDOT-2.5A	5/32"	1/8"	19.0	20.3	14.29
C279PPSDOT-4A	1/4"	1/8"	19.0	20.3	14.29
C279PPSDOT-4B	1/4"	1/4"	19.0	24.3	14.29
C279PPSDOT-4C	1/4"	3/8"	19.0	26.3	17.46
C279PPSDOT-6A	3/8"	1/8"	26.2	26.6	19.00
C279PPSDOT-6B	3/8"	1/4"	26.2	29.6	19.00
C279PPSDOT-6C	3/8"	3/8"	26.2	31.6	19.00
C279PPSDOT-6D	3/8"	1/2"	26.2	35.6	22.23
C279PPSDOT-8A	1/2"	1/8"	28.8	29.5	23.80
C279PPSDOT-8B	1/2"	1/4"	28.8	32.5	23.80
C279PPSDOT-8C	1/2"	3/8"	28.8	33.5	23.80
C279PPSDOT-8D	1/2"	1/2"	28.8	37.5	23.80
C279PPSDOT-10C	5/8"	3/8"	29.6	32.0	23.80
C279PPSDOT-10D	5/8"	1/2"	29.6	35.0	23.80
C279PPSDOT-12D	3/4"	1/2"	39.1	41.9	28.57




C272PPSDOT MALE SWIVEL RUN TEE

PART NUMBER	Tube O.D.	MPT	A	B	HEX
C272PPSDOT-2.5X	5/32"	1/16"	23.4	41.2	14.29
C272PPSDOT-2.5A	5/32"	1/8"	23.4	41.2	14.29
C272PPSDOT-2.5B	5/32"	1/4"	27.4	41.2	14.29
C272PPSDOT-4A	1/4"	1/8"	23.4	41.2	14.29
C272PPSDOT-4B	1/4"	1/4"	27.4	41.2	14.29
C272PPSDOT-4C	1/4"	3/8"	29.4	41.2	17.46
C272PPSDOT-6A	3/8"	1/8"	26.6	52.4	19.00
C272PPSDOT-6B	3/8"	1/4"	29.6	52.4	19.00
C272PPSDOT-6C	3/8"	3/8"	31.6	54.4	19.00
C272PPSDOT-6D	3/8"	1/2"	35.6	52.4	22.23
C272PPSDOT-8B	1/2"	1/4"	31.5	57.6	19.00
C272PPSDOT-8C	1/2"	3/8"	33.5	57.6	19.00
C272PPSDOT-8D	1/2"	1/2"	37.5	57.6	22.23
C272PPSDOT-10C	5/8"	3/8"	37.8	66.8	23.80
C272PPSDOT-10D	5/8"	1/2"	40.8	66.8	23.80



C286PPDOT FEMALE BULKHEAD

PART NUMBER	Tube O.D.	FPT	UNF	A
C286PPDOT-5B	5/32"	1/4"	1/2-20	31.0
C286PPDOT-4A	1/4"	1/8"	9/16-18	27.5
C286PPDOT-4B	1/4"	1/4"	9/16-18	32.4
C286PPDOT-6B	3/8"	1/4"	7/8-14	34.5
C286PPDOT-6C	3/8"	3/8"	7/8-14	36.9
C286PPDOT-8C	1/2"	3/8"	1-12	37.1
C286PPDOT-8D	1/2"	1/2"	1-12	41.2





NYLON AIR BRAKE TUBING



CONSTRUCTION

- Type A** tubing consists of a single wall extrusion of pelletized homopolymer or copolymer of polyamide containing additives that provide heat and light resistance.
- Type B** tubing consists of a core extrusion with one or two layers of pelletized polyamide containing additives that provide heat resistance. The core is fiber reinforced using a spiral filament applied in each direction and sheathed with a protective layer of chemical resistant homopolymer or copolymer of polyamide containing additives for heat and light resistance. The cover is fusion bonded to the core tube through the interstices of the spiral yarn reinforcement. The core tube and cover are of contrasting colors.

APPLICATIONS

- NAB150-Series** polyamide tubing is for use in air brake systems. Non-reinforced tubing is designated Type A and reinforced tubing Type B. This tubing is intended for brake system connections that maintain a basically fixed relationship between couplings during vehicle operation.
- Air Tanks:** Stores Air for Braking, Suspension, Sliders, etc.
- Air Brake Systems:** Chassis (Provide Stopping Power for Truck/Trailer)
- Air Brake Systems:** Brake Chamber (Provide Stopping Power for Truck/Trailer)
- Tire Inflation Systems:** Keeps Tires at Optimal Pressure
- Air Ride Systems:** Provides Air Suspension in Seat, Cab, and Vehicle



RANGES

- 150 psig maximum (1030 KPa)
- 40°F to +200°F (-40°C to +93°C)



Part No.:	Nominal O.D. (In)	Outside Dia. (In)	Inside Dia. (In)	Wall Thickness (In)	Min. Burst Pressure @ 73°F	Min. Bend Radius (In)	Max Stiffness (lbs)
NAB150-2A	1/8"	.128/.122	0.079	.026/.020	1000	0.37	1
NAB150-2.5A	5/32"	.153/.159	0.092	.029/.035	1200	0.5	1
NAB150-3A	3/16"	.185/.191	0.118	.032/.038	1200	0.75	1
NAB150-4A	1/4"	.253/.247	0.17	.043/.037	1200	1	2
NAB150-5A	5/16"	.316/.308	0.232	.044/.036	1000	1.25	6
NAB150-6B	3/8"	.379/.371	0.251	.066/.058	1400	1.5	8
NAB150-8B	1/2"	.505/.495	0.376	.066/.058	950	2	20
NAB150-10B	5/8"	.630/.620	0.441	.097/.087	900	2.5	50
NAB150-12B	3/4"	.755/.745	0.566	.097/.087	800	3	80

COLOR	CODE
BLACK	BK
BLUE	BL
BROWN	BR
GREEN	GR
ORANGE	OR
PURPLE	PR
RED	RD
SILVER	SL
TAN	TN
YELLOW	YL
WHITE	WT

Robo-Fit Example Part No.:	NAB150-6B-500-BK
Product Description:	Nylon Air Brake Tubing, 3/8", Black, Type B, 500' Reel



⚠ WARNING: This product can expose you to chemicals including **Nickel and Nickel Compounds** which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov



MADE IN USA




AIR BRAKE HOSE ENDS

CONSTRUCTION	• CA360 Brass 
APPLICATIONS	• Air Brake Systems 
RANGES	• Temperature Range: -40° to 200° F. • Pressure Range: Up to 150 PSI 




Assembly Instructions

1. Slide the nut/spring guard over the J1402 air brake hose.
2. Slide the sleeve over the hose, making sure the tapered edge of the sleeve is facing the fitting body (shown below).
3. Push the hose over the fitting body until the hose bottoms out.
4. Tighten the nut until there is contact with the fitting body's hex. Completed assembly shown below.



Application Details:





Transportation Air Brake Systems.
Use with J1402 Air Brake Hose



NOTES


- Fittings meet SAE and DOT FMVSS 571.106
- Non-stock items and special parts are available on a quotation basis.
- Configurations and dimensions are subject to change without notice.

 **WARNING:** Products offered by Robo-Fit can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov

360A Hose Sleeve 	361A Hose Nut 	361AG Spring Guard Nut 
362A Union Hose Splicer 	366A Female Hose Swivel Connector 	368A Male Hose Connector 
370A Hose Nut w/ Spring Guard 	371AS Hose Spring Guard 	378A Hose Connector with Spring 
388A Hose Adapter 		


360A HOSE SLEEVE

PART NUMBER	HOSE	A
360A-6	3/8"	.69
360A-8	1/2"	.69




362A UNION HOSE SPLICER

PART NUMBER	HOSE	A
362A-6	3/8"	2.95
362A-8	1/2"	2.96




361A HOSE NUT

PART NUMBER	HOSE	A	HEX
361A-6	3/8"	1.18	13/16"
361A-8	1/2"	1.125	1-1/4"



366A FEMALE SWIVEL HOSE CONNECTOR

PART NUMBER	HOSE	THD	A
366A-6C	3/8"	3/4-20	2.30
366A-8D	1/2"	7/8-20	2.36





**Use w/ 388A Series*




361AG SPRING GUARD NUT

PART NUMBER	HOSE	A	HEX
361AG-6	3/8"	1.22	1-1/16"
361AG-8	1/2"	1.19	1-1/4"




368A MALE HOSE CONNECTOR

PART NUMBER	HOSE	MPT	A	HEX
368A-6B	3/8"	1/4"	2.25	1"
368A-6C	3/8"	3/8"	2.38	1"
368A-6D	3/8"	1/2"	2.44	1"
368A-8C	1/2"	3/8"	2.24	1-1/8"
368A-8D	1/2"	1/2"	2.40	1-1/8"




371A HOSE NUT WITH SPRING GUARD

PART NUMBER	HOSE	A	HEX
371A-6	3/8"	3.50	13/16"
371A-8	1/2"	3.75	1-1/4"




388A HOSE ADAPTER

PART NUMBER	STRAIGHT THREAD	MPT	A	HEX
388A-12B	3/4-20	1/4"	1.06	3/4"
388A-12C	3/4-20	3/8"	1.12	3/4"
388A-14C	7/8-20	3/8"	1.19	7/8"
388A-14D	7/8-20	1/2"	1.38	7/8"




371AS HOSE SPRING GUARD

PART NUMBER	HOSE	A
371AS-6	3/8"	2.75
371AS-8	1/2"	3.00



378A HOSE CONNECTOR W/ SPRING GUARD

PART NUMBER	HOSE	MPT	A	HEX
378A-6B	3/8"	1/4"	4.75	1"
378A-6C	3/8"	3/8"	4.75	1"
378A-6D	3/8"	1/2"	4.88	1"
378A-8C	1/2"	3/8"	5.12	1-1/8"
378A-8D	1/2"	1/2"	4.88	1-1/8"



AIR BRAKE 10 mm (3/8") SAE J1402A DOT KX MADE IN USA



CONSTRUCTION

- TUBE: EPDM, ARPM - Class C
- COVER: EPDM, ARPM - Class C

APPLICATIONS



- Air Brake Systems
- D.O.T. FMVSS 106 SAE J1402, TYPE A
- Meets or Exceeds All of the Industry Standards

RANGES

- Temperature Range: -40° to 200° F.
- Pressure Range: Min Burst 900 psi





REINFORCEMENT: 4-Spiral Polyester Yarn

- Minimum Burst Exceeds 900 psi
- More Flexible than Braid Reinforced Hose
- Easier to Route Assemblies
- Easier to Coil and Handle
- Maintains its Flexibility
- Kink Resistant



Assembly Instructions

1. Slide the nut/spring guard over the J1402 air brake hose.
2. Slide the sleeve over the hose, making sure the tapered edge of the sleeve is facing the fitting body (shown below).
3. Push the hose over the fitting body until the hose bottoms out.
4. Tighten the nut until there is contact with the fitting body's hex. Completed assembly shown below.



PART NUMBER	Nominal I.D.	Nominal O.D.	Min Bend Radius	Reinforcement Spirals	Lb/ft
J1402-HR-6-250	3/8"	.75"	2.25"	4	.17
J1402-HR-6-500	3/8"	.75"	2.25"	4	.17
J1402-HR-8-250	1/2"	.88"	3.00"	4	.20
J1402-HR-8-500	1/2"	.88"	3.00"	4	.20

WARNING: Products offered by Robo-Fit can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov



DRAIN & TRUCK VALVES

CONSTRUCTION	• CA360 Brass • CA377 Brass	
APPLICATIONS	• In Line Shut Off • Air Drain • Drain Valves	
RANGES	• Maximum Pressure : 30 PSIG • Maximum Pressure: 150 PSI • Temperature: -20° F to +250° F	

	FEATURES/BENEFITS
	• Forged Brass Body • Plug Style Valve • Economical Tight Shut Off • Made in USA

NOTES

- Parts that include “PBF” are supplied as low lead compliant.
- Part numbers without the “PBF” distinction are NOT lead free compliant.
- Non-stock items and special parts are available on a quotation basis.
- Configurations and dimensions are subject to change without notice.



WARNING: Products offered by Robo-Fit can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov

247V MPT INTERNAL SEAT DRAIN VALVE

PART NUMBER	MPT
247V-J	1/8"
247V-L	1/4"
247V-N	3/8"
247V-P	1/2"



H35C SPRING BOTTOM DRAIN VALVE

PART NUMBER	MPT	P.S.I.G.
H35C-J	1/8"	150
H35C-L	1/4"	150


**Valve Shown in "Open" Position*

**Rated 150 P.S.I.G.*



30C SPRING BOTTOM DRAIN VALVE

PART NUMBER	MPT	P.S.I.G.
30C-J	1/8"	30
30C-L	1/4"	30
30C-N	3/8"	30
30C-P	1/2"	30




**Valve Shown in "Closed" Position*

**Rated 30 P.S.I.G.*

31C SPRING BOTTOM DRAIN VALVE

PART NUMBER	MPT	P.S.I.G.
31C-J	1/8"	30
31C-L	1/4"	30
31C-N	3/8"	30
31C-P	1/2"	30



**Valve Shown in "Open" Position*

**Rated 30 P.S.I.G.*

H30C SPRING BOTTOM DRAIN VALVE

PART NUMBER	MPT	P.S.I.G.
H30C-J	1/8"	150
H30C-L	1/4"	150



**Valve Shown in "Open" Position*

**Rated 150 P.S.I.G.*


38D MACHINED DRAIN COCK

PART NUMBER	MPT	FLOW DIA.
38D-DCR	1/4"	.156

**Temperature Range:*

-30° to +250°F

**Rated 150 P.S.I.G.*



201DH 90° BEADED DRAIN COCK

PART NUMBER	HOSE BIBB	MPT
201DH	3/8"	1/4"



320D EXTERNAL SEAT DRAIN COCK

PART NUMBER	MPT
320D	1/8"
321D	1/4"
322D	3/8"



421D EXTENSION EXTERNAL SEAT DRAIN

PART NUMBER	MPT
421D	1/4"



97V HOSE TO MPT RISING STEM VALVE

PART NUMBER	SIDE PORT	BOTTOM PORT	HANDLE
P97V-6N	3/8" MLT HOSE	3/8" MPT	PIN
97V-6N	3/8" MLT HOSE	3/8" MPT	ROUND
97V-6N1	3/8" BIB HOSE	3/8" MPT	ROUND
P97V-10N	5/8" BIB HOSE	3/8" MPT	PIN
97V-10N	5/8" BIB HOSE	3/8" MPT	ROUND
97V-10P	5/8" BIB HOSE	1/2" MPT	ROUND
907V-10P	5/8" BIB HOSE	1/2" MPT	ROUND
907V-12N	3/4" BIB HOSE	3/8" MPT	ROUND
907V-12P	3/4" BIB HOSE	1/2" MPT	ROUND



**Pin Handle*



**Round Handle*



**Beaded Hose Barb*



**Beaded Hose Barb*

**Maximum Pressure:*

200 P.S.I.G.

**Temperature Rating:*

-20° to +250° F

90V FPT X MPT RISING STEM VALVE

PART NUMBER	SIDE PORT	BOTTOM PORT	HANDLE
90V-N	3/8" FPT	3/8" MPT	ROUND
900V-N	3/8" FPT	3/8" MPT	ROUND
90V-NP	3/8" FPT	1/2" MPT	ROUND
900V-P	1/2" FPT	1/2" MPT	ROUND



95V FLARE X MPT RISING STEM VALVE

PART NUMBER	SIDE PORT	BOTTOM PORT	HANDLE
95V-6N	3/8" FLARE	3/8" MPT	ROUND
P95V-6N	3/8" FLARE	3/8" MPT	PIN
95V-10P	5/8" FLARE	1/2" MPT	ROUND
905V-10P	5/8" FLARE	1/2" MPT	ROUND
95V-P10	1/2" MPT	5/8" FLARE	ROUND



**Flare x MPT*



**MPT x Flare*



MADE IN USA



SELECTOR VALVES

CONSTRUCTION	• CA377 Brass	
APPLICATIONS	• Operation in gasoline, oil, air, water and detergent systems. • Fuel Switching/Tank Selection	
RANGES	• Maximum Pressure: 30 PSIG on 100/200 • Maximum Pressure: 15 PSIG on SK1036 Temperature: -40°F to +180° F	



3 & 4-WAY SELECTOR VALVES

The 100 & 200 Series Non-Lubricated Plug Valves are designed to operate in systems where instantaneous port selection is desired. Since lubricants are not used, re-lubrication is not required. There is no lubricant to freeze and lock the valve or to contaminate fine fluids. The o-ring sealed cap and stem eliminate leakage to the atmosphere. The mating

100 SERIES is standard with a pointer lever to indicate the desired porting selection and can be rotated 360°. A number of special body porting patterns, flow combinations, “Click” or “Click-Stop” arrangements and special stem lengths are available. Designed for panel or bracket mounting.


200 SERIES is standard with a pointer lever and an audible “Click Mechanism.” This arrangement assures proper porting selection by sound or touch without looking at the valve. This construction is highly desirable when the operator’s visual attention cannot be distracted or for remote valve locations. The valve rotates 360° with “Click” intervals spaced every 90°. Designed for panel or bracket mounting.

Fluid Port Size	Diameter
1/8" & 1/4"	9/32" (.281)
3/8"	5/16" (.312)

 **WARNING:** Products offered by Robo-Fit can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov

THREE-WAY SELECTOR VALVES (SIDE OUTLET)

PART NUMBER	Port Size	Click Stop	# of Ports	Stem Length
210C-J	1/8" FPT	YES	3	1 3/8"
110C-L	1/4" FPT	NO	3	1 3/8"
210C-L	1/4" FPT	YES	3	1 3/8"
210C-LS	1/4" FPT	YES	3	3/4"
210C-LM	1/4" FPT	YES	3	2 3/8"
110C-N	3/8" FPT	NO	3	1 3/8"
210C-N	3/8" FPT	YES	3	1 3/8"




OPENINGS:

- Handle Pointer Over A: Valve Open A-C
- Handle Pointer Over C: Valve Open B-C
- Handle Pointer Over B: Valve "OFF"
- Handle Pointer Over Bracket: Valve "OFF"

FOUR-WAY SELECTOR VALVES

PART NUMBER	Port Size	Click Stop	# of Ports	Stem Length
100C-L	1/4" FPT	NO	4	1 3/8"
200C-L	1/4" FPT	YES	4	1 3/8"
100C-N	3/8" FPT	NO	4	1 3/8"
200C-N	3/8" FPT	YES	4	1 3/8"
205C-L	1/4" FPT	YES	4	2 3/8"
205C-N	3/8" FPT	YES	4	2 3/8"
215C-L	1/4" FPT	YES	4	3 3/4"
115C-N	3/8" FPT	NO	4	3 3/4"
215C-N	3/8" FPT	YES	4	3 3/4"




OPENINGS:

- Handle Pointer Over A: Valve Open A-D
- Handle Pointer Over C: Valve Open C-D
- Handle Pointer Over B: Valve Open B-D
- Handle Pointer Over Bracket: Valve "OFF"

SIX PORT VALVES

PART NUMBER	FEMALE PIPE THREAD	FEMALE PIPE THREAD	LENGTH OF STEM	TYPE
	1-2-3	4-5-6		
SK-1031	1/2"	3/8"	5/16"	1
SK-1036	1/2"	3/8"	13/16"	1
SP-2381-CM	1/2"	3/8"	5/16"	2
SP-2483-CM	1/2"	3/8"	5/16"	3
SP-2486-CM	1/2"	3/8"	13/16"	3

“Designed primarily for diesel engine applications where a fuel return or spill back is required. These valves are widely used in the trucking and marine industry and by manufacturers of diesel generating plants.”



TYPE 1	TYPE 2	TYPE 3
Maximum Handle Travel 180° Mounting Pads for Bolt Mounting	Maximum Handle Travel 90° Mounting Pads for Bolt Mounting	Maximum Handle Travel 90° Mounting Pads for Bolt Mounting
OPENINGS	OPENINGS	OPENINGS
Handle Pointer Over 2: (All Ports Closed)	Handle Pointer Over 3: (Open: 1-3 & 4-6, Closed 2 & 5)	Handle Pointer Over 1: (Open: 1-3 & 4-6, Closed 2 & 5)
Handle Pointer Over 3: (Open: 1-3 & 4-6, Closed 2 & 5)	Handle Pointer Over 2: (Open: 2-3 & 5-6, Closed 1 & 4)	Handle Pointer Over 3: (Open: 2-3 & 5-6, Closed 1 & 4)
Handle Pointer Over 1: (Open: 2-3 & 5-6, Closed 1 & 4)		






PANEL MOUNT BALL VALVES

CONSTRUCTION	• CA360 Brass	
APPLICATIONS	• Air Brake Systems	
RANGES	• Temperature Range: -40°F to 300°F -40°C to +93°C • Pressure Range: 1500psig	

	FEATURES/BENEFITS
	• Bar-Stock Brass Body • Double O-Ring Stem Seal • 20,000 Leak Free Cycles • Blow Out Proof Stem • Metal Retainer Seal • Made in USA  • Guaranteed Quality

NOTES

- Parts that include “PBF” are supplied as low lead compliant.
- Part numbers without the “PBF” distinction are NOT lead free compliant.
- Non-stock items and special parts are available on a quotation basis.
- Configurations and dimensions are subject to change without notice.




 **WARNING:** Products offered by Robo-Fit can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov


3222BV SERIES 3-WAY BALL VALVES, FPT x FPT x FPT

PART NUMBER	PORT A	PORT B	PORT C	CV	ORIFICE DIA.
3222BV-LLXL	1/4" FPT	1/4" FPT	1/4" FPT	1.57	0.250

**Valves to Read: Left, Right, Middle*



PART NUMBER	PORT A	PORT B	PORT C	CV	ORIFICE DIA.
3222BV-LLXL-8	1/4" FPT	1/4" FPT	1/4" FPT	1.57	0.250



MADE IN USA



INDUSTRIAL BALL VALVES

CONSTRUCTION	• CA360 Brass • CA377 Brass	
APPLICATIONS	• Fuel Tank Shut-Off • Coolant Stop • Diverter Valves • Hydraulic or Pneumatic	
RANGES	• Maximum Pressure 600 PSI • Temperature to 300° F • Saturated Steam 150 PSI	

	FEATURES/BENEFITS
	• Forged Brass Body • Double O-Ring Stem Seal • Stem Seal Never Needs Tightening • 20,000 Leak Free Cycles • Blow Out Proof Stem • Made in USA 

NOTES

- Parts that include “PBF” are supplied as low lead compliant. 
- Part numbers without the “PBF” distinction are NOT lead free compliant.
- Non-stock items and special parts are available on a quotation basis.
- Configurations and dimensions are subject to change without notice.

 **WARNING:** Products offered by Robo-Fit can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov



Double o-ring protection provides over 20,000 cycles without leakage!

The exclusive stem seal design that never needs tightening!

160BV MALE TO FEMALE BALL VALVE

PART NUMBER	MPT	FPT
160BV-L	3/8"	3/8"
160BV-P	1/2"	1/2"
160BV-R	3/4"	3/4"
160BV-S	1"	1"



120BV 3-WAY FEMALE BALL VALVE

PART NUMBER	FPT	CV
120BV-L	1/4"	5.2
120BV-N	3/8"	5.5
120BV-P	1/2"	5.5



Pressure Rating:


***Bottom Port as Inlet: 500 P.S.I.**

***Side Port as Inlet: 100 P.S.I.**



162BV FEMALE BALL VALVE

PART NUMBER	FPT	FPT
162BV-L	3/8"	3/8"
162BV-P	1/2"	1/2"
162BV-R	3/4"	3/4"
162BV-S	1"	1"



190BV 2-WAY 90° BALL VALVE

PART NUMBER	FPT	MPT	CV
190BV-L	1/4"	1/4"	5.2
190BV-N	3/8"	3/8"	5.5
190BV-P	1/2"	1/2"	5.5



Pressure Rating:

***Bottom Port as Inlet: 600 P.S.I.**

***Side Port as Inlet: 100 P.S.I.**



MADE IN USA



CHECK VALVES

CONSTRUCTION	•CA360 Brass	
APPLICATIONS	•Unidirectional Flow Applications	
RANGES	•Maximum Pressure : 1000 PSIG •Temperature: -40° F to +300° F (Standard) -40° F to +400° F (Special)	

	FEATURES/BENEFITS
•Self Centering Seal Design •O-Ring Soft Seat / Metal Back Up Seat •Zero Leakage •1/3 PSI Cracking Pressure Standard •Optional Cracking Pressures Available •Made in USA •Guaranteed Quality	

NOTES

- Parts that include “PBF” are supplied as low lead compliant.
- Part numbers without the “PBF” distinction are NOT lead free compliant.
- Non-stock items and special parts are available on a quotation basis.
- Configurations and dimensions are subject to change without notice.

WARNING: Products offered by Robo-Fit can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Quality Matters!
Our check valves are proudly
Made in America.

741CV MPTF x MPTF

PART NUMBER	MPT	OAL
741CV-J	1/8"	1.20 ± .03



750CV2 FPT x MPT

PART NUMBER	FPT	MPT
750CV2-JXJ	1/8"	1/8"
750CV2-LXL	1/4"	1/4"
750CV2-NXN	3/8"	3/8"
750CV2-PXP	1/2"	1/2"




745CV FLARE x MPTF

PART NUMBER	FLARE	MPTF
745CV-4J	1/4"	1/8"
745CV-J4	1/8"	1/4"



751CV MPT x MPT

PART NUMBER	FPT	FPT
751CV-JXJ	1/8"	1/8"
751CV-LXL	1/4"	1/4"
751CV-NXN	3/8"	3/8"
751CV-PXP	1/2"	1/2"



750CV1 MPT x FPT

PART NUMBER	MPT	FPT
750CV1-JXJ	1/8"	1/8"
750CV1-LXL	1/4"	1/4"
750CV1-NXN	3/8"	3/8"
750CV1-PXP	1/2"	1/2"



752CV FPT x FPT

PART NUMBER	MPT	MPT
752CV-JXJ	1/8"	1/8"
752CV-LXL	1/4"	1/4"
752CV-NXN	3/8"	3/8"
752CV-PXP	1/2"	1/2"



750CV Series Flow Direction:

*750CV1: Flows From Male to Female Thread

*750CV2: Flows From Female to Male Thread



MADE IN USA



MINIATURE BALL VALVES

CONSTRUCTION	• CA360 Brass	
APPLICATIONS	•In Line Shut-Off •Air Lines •Water Lines ⚠ Not intended for potable water	
RANGES	•Maximum Pressure : 1000 PSIG •Temperature: -40° F to +300° F (Standard) -40° F to +400° F (Special)	

FEATURES/BENEFITS

- Bar-Stock Brass Body
- Blow Out Proof Stem
- Viton Stem Seal
- Standard Lever Handle
- Optional Round Handle
- Nickel Plated Brass Ball
- Made in USA
- Guaranteed Quality




STANDARD LEVER HANDLE	ALTERNATIVE ROUND HANDLE
TO ORDER VALVES WITH THE ROUND HANDLE (SHOWN TO THE RIGHT ABOVE) ADD AN “R” TO THE SERIES PART NUMBER.	EX: 352BV-J: Standard Part Number for <u>Lever Handle</u> 352BVR-J: Special Part Number for <u>Round Handle</u>



MADE IN USA


350BV FPT x MPT

PART NUMBER	FPT	MPT	CV	ORIFICE
350BV-J	1/8"	1/8"	1.39	.250
350BV-JXL	1/8"	1/4"	1.39	.250
350BV-L	1/4"	1/4"	1.57	.250
350BV-LXN	1/4"	3/8"	1.57	.250




355BV FLARE x MPT

PART NUMBER	FLARE	MPT	CV	ORIFICE
355BV-4J	1/4"	1/8"	1.39	.250
355BV-4L	1/4"	1/4"	1.57	.250
355BV-6J	3/8"	1/8"	1.57	.250
355BV-6L	3/8"	1/4"	1.57	.250
355BV-6N	3/8"	3/8"	2.74	.250




351BV MPT x MPT

PART NUMBER	MPT	MPT	CV	ORIFICE
351BV-J	1/8"	1/8"	1.39	.250
351BV-JXL	1/8"	1/4"	1.39	.250
351BV-L	1/4"	1/4"	1.57	.250
351BV-N	3/8"	3/8"	1.57	.250




356BV FLARE x FLARE

PART NUMBER	FLARE	CV	ORIFICE
356BV-4	1/4"	1.57	.250
356BV-6	3/8"	1.57	.250




352BV FPT x FPT

PART NUMBER	FPT	FPT	CV	ORIFICE
352BV-J	1/8"	1/8"	1.39	.250
352BV-L	1/4"	1/4"	1.57	.250
352BV-JXL	1/8"	1/4"	1.39	.250




357BV HOSE BARB x FLARE

PART NUMBER	HOSE BARB	MPT	CV	ORIFICE
357BV-4J	1/4"	1/8"	1.39	.250
357BV-4L	1/4"	1/4"	1.57	.250
357BV-5L	5/16"	1/4"	1.57	.250
357BV-6L	3/8"	1/4"	1.57	.250
357BV-6N	3/8"	3/8"	2.74	.250



353BV COMPRESSION x MPT

PART NUMBER	O.D. TUBE	MPT	CV	ORIFICE
353BV-4J	1/4"	1/8"	1.39	.250
353BV-4L	1/4"	1/4"	1.57	.250
353BV-6L	3/8"	1/4"	1.57	.250




354BV COMPRESSION BOTH ENDS

PART NUMBER	O.D. TUBE	CV	ORIFICE
354BVS-2	1/8"	1.39	.250
354BVS-4	1/8"	1.57	.250
354BVS-6	1/4"	2.74	.250




358BV FLARE x FPT

PART NUMBER	FLARE	FPT	CV	ORIFICE
358BV-4J	1/4"	1/8"	1.39	.250
358BV-4L	1/4"	1/4"	1.57	.250



⚠ WARNING: Products offered by Robo-Fit can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov



PUSH BUTTON VALVES

CONSTRUCTION	•CA377 Brass	
APPLICATIONS	•Fuel Sampling Valve •Pressure Relief •Valve Injection •Drain Valve •Holds Vacuum	
RANGES	•Maximum Pressure : 500 PSIG •Temperature: -40° to 300° F (Standard) -40° to 400° F (Special)	

FEATURES/BENEFITS

- Instantaneous On/Off
- Multiple O-Ring Options
- Flexible End Connection
 - Forged Brass Body
 - 90° Configuration
 - Made in USA
- Guaranteed Quality



PB2 FPT x FPT

PART NUMBER	FPT	FPT	STYLE	OPERATOR
PB2-J	1/8"	1/8"	STANDARD	PUSH BUTTON
PB2-3A-J	1/8"	1/8"	PANEL MOUNT	PUSH BUTTON
PB2-L	1/4"	1/4"	STANDARD	PUSH BUTTON
PB2-3A-L	1/4"	1/4"	PANEL MOUNT	PUSH BUTTON

 **WARNING:** Products offered by Robo-Fit can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov



Closed Position Shown
Push Button Toward the Valve
Body for Sampling



MADE IN USA



ROBO-FIT PRODUCT WARRANTY

Robo-Fit warrants that our products are free from defects in material and workmanship. However, please note that no other warranties, express or implied, including warranties of merchantability, are provided. Liability for defective materials or workmanship is limited to the replacement or repair of defective products, subject to the condition that such products are returned within 30 days after receipt. Any repairs made by the Purchaser or at their request will not be covered by this warranty. Please be aware that Robo-Fit will not be responsible for any consequential or other damages or expenses incurred as a result of the use of our products. While our published literature reflects all current design, dimensions, and performance data at the time of initial publication, please note that modifications may be made on an ongoing basis to upgrade our products. Such modifications may result in changes to the design, dimensions, and/or performance of the products as shown in this catalog. Please note that while working pressures and other technical information have been prepared from sources deemed reliable, Robo-Fit cannot assume responsibility for the accuracy of this information under varied field conditions. Such information should be considered a recommendation only, rather than a guarantee.



WARNING: Products offered by Robo-Fit can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

As of January 4, 2014, Federal Public Law 111-380 prohibits the sale of plumbing fixtures with a wetted surface area containing more than a weighted average of 0.25% lead. Robo-Fit parts are to be used only for non-potable services, unless they have been given the “PBF” distinction on their corresponding part numbers. It is incumbent upon Robo-Fit customers to determine whether or not the products they use are compliant with Federal Public Law 111-380.



ROBO-FIT, LLC

2275 E. ENTERPRISE PKWY

TWINSBURG, OHIO 44087

(440) 893-9878

WWW.ROBO-FIT.COM

Part No.	Page
100A	4
100-45A	4
101A	4
102A	4
103A	5
104A	5
108A	5
109A	5
109AS	5
109CS	5
110FB	5
110A	6
111A	6
112A	6
113A	6
113RB	7
116A	7
116AL	7
116AM	8
117A	8
119A	8
120A	8
121A	8
121AS	8
122A	9
123A	9
124A	9
127A	9
T9	9
129A	9
RF	12
201A	16
201AB	16
201BF	16
209A	17
209A-SV	13
122AS	13
209ASF	13
209ASF-45°	14
209ASF-37°	14

Part No.	Page
HE1	18
HE1-45	18
269HB	18
HM	19
HM-90	19
HBT2	19
122RWA	19
122LWA	19
209RWA	19
209LWA	19
BF	20
301	23
301-SV	23
302	23
303	23
304	23
305	24
306	24
307	24
308	24
309	24
3099	25
3099-SV	25
310	25
1000B	25
B1/B2	28
C1	28
DE3	28
E1	28
E1-45	29
E2	29
ER2	30
E3	30
E4	30
ES4	30
K1	30
41AS	31
NSE1	31
N1	31
N2	31

Part No.	Page
N4	31
NS4	31
N5	32
P2	32
T1	32
T2	33
T3	33
T4	34
U1	34
U2	34
U3	35
U4	35
US4	35
59A	39
60NAB	39
61NAB	39
62NAB	39
62NABH	39
64NAB	39
65NAB	40
66NAB	40
68NAB	40
68NABH	40
69NAB	40
70NAB	41
71NAB	41
72NAB	41
79NAB	41
259PPDOT	44
262PPDOT	44
262PPBHDOT	44
264PPDOT	44
265PPDOT	44
266PPDOT	44
268PPDOT	45
2688PPDOT	45
269PPDOT	45
269PPSDOT	45
270PPDOT	46
270PPSDOT	46

Part No.	Page
271PPDOT	46
271PPSDOT	46
272PPDOT	46
272PPSDOT	46
277PPDOT	47
277PPSDOT	47
279PPDOT	47
279PPSDOT	47
283PPDOT	48
286PPDOT	48
C259PPDOT	51
C262PPDOT	51
C262PPBHDOT	51
C264PPDOT	51
C265PPDOT	51
C266PPDOT	51
C268PPDOT	52
C2688PPDOT	52
C269PPSDOT	52
C270PPSDOT	52
C271PPSDOT	53
C272PPSDOT	53
C277PPSDOT	53
C279PPSDOT	53
C286PPDOT	53
NABT	55
360A	58
361A	58
361AG	58
362A	58
366A	58
368A	58
371A	59
371AS	59
378A	59
388A	59
J1402	
247V	46
30C	46
31C	46

Part No.	Page
H30C	62
H35C	62
38D	62
201DH	62
320D	62
421D	63
90V	63
95V	63
97V	63
100C	65
110C	65
115C	65
205C	65
210C	65
215C	65
SK-1031	66
SK-1036	66
SP-2381-CM	66
SP-2483-CM	66
SP-2486-CM	66
3222BV	68
120BV	70
160BV	70
162BV	70
190BV	70
741CV	72
745CV	72
750CV	72
751CV	72
752CV	72
350BV	74
351BV	74
352BV	74
353BV	74
354BV	74
355BV	74
356BV	74
357BV	74
358BV	74
PB2	75


PIPE THREAD SPECIFICATIONS

National Pipe Thread: NPT & NPTF

NPTF (Dry Seal Pipe Threads)

Dry seal pipe threads are made to the American National Standards Institute (ANSI) B1.20.3 specification and are designed to seal pressure tight joints. NPTF threads are commonly used in fluid power applications.

NPTF thread roots are wider than their crests. When the threads are wrenched together, the roots crush the sharper crest of the mating threads. This thread deformation forms a metal to metal seat, ensuring a leak free connection. To determine the nominal pipe size, measure the thread diameter and subtract 1/4". Use of thread sealant is still recommended to ensure a leak free connection.



Thread Type	1/8	1/4	3/8	1/2	3/4	1
NPTF	1/8-27	1/4-18	3/8-18	1/2-14	3/4-14	1-11-1/2

NPT (Tapered Pipe Threads)

Non-dry seal pipe threads are made to the American National Standards Institute (ANSI) B1.20.1 specification. NPT threads seal at their respective flanks, leaving the possibility of having clearance between the roots and crests. NPT threads cannot ensure the prevention spiral leakage, and require the use of pipe sealant for all applications. To determine the nominal pipe size, measure the thread diameter and subtract 1/4".

The first two full threads ($\pm 1/2$ THD.) should remain free of pipe sealant to allow for thread engagement when wrenching an assembly.



Ask about our volume vibra-sealing capabilities!
We vibra-seal our fittings in house.

FITTING NUMBERING SYSTEM

O.D. TUBE SIZE

-2	1/8"
-3	3/16"
-4	1/4"
-5	5/16"
-6	3/8"
-7	7/16"
-8	1/2"
-10	5/8"
-12	3/4"
-14	7/8"
-16	1"

PIPE SIZE

-A	1/8"
-B	1/4"
-C	3/8"
-D	1/2"
-E	3/4"
-F	1"


Each part number indicates the style of the fitting and the size, the letters and/or numbers preceding the dash indicate the style and the letters and/or numbers following the dash indicate the size. Fitting part numbers will always read tube to pipe ends.

For example, **E1-10D** (shown below) is an extruded el-

E1 = 90° Male Flare Elbow

10 = 5/8" O.D.

D = 1/2" MPT



STRAIGHT THREAD SIZE CHART

Fitting Type (O.D. Tube Size)	1/8	3/16	1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1
45° Flare	5/16-24	3/8-24	7/16-20	1/2-20	5/18-18	11/16-16	3/4-16	7/8-14	1-1/16-14	1-1/4-12	-
Inverted Flare	5/16-28	3/8-24	7/16-24	1/2-20	5/18-18	11/16-18	3/4-18	7/8-18	1-1/16-16	1-3/16-16	-
Air Brake (DOT)	-	-	7/16-24	-	17/32-24	-	11/16-20	13/16-18	1-18	-	1-1/4-16
Compression (Non DOT)	5/16-24	3/8-24	7/16-24	1/2-24	9/16-24	5/8-24	11/16-20	13/16-18	1-18	1-1/8-18	1-1/4-18
Poly-Fit	-	-	3/8-24	7/16-24	1/2-24	-	11/16-20	-	1-1/8-18	-	-

FITTING CONFIGURATION NUMBERING SYSTEM

Configuration #	Description	Photo
60	Sleeve	
61	Nut	
62	Union (Tube Both Ends)	
64	Union Tee (Tube All Ends (3))	
65	90° Union Elbow (Tube Both Ends)	
66	Female Connector (Tube to FPT)	
68	Male Connector (Tube to MPT)	
69	90° Male Elbow (Tube to MPT)	
70	90° Female Elbow (Tube to FPT)	
71	Male Run Tee (Tube to MPT to Tube)	
72	Male Branch Tee (Tube to Tube to MPT)	
77	Female Branch Tee (Tube to FPT)	
79	45° Male Elbow (Tube to MPT)	

***71/72/77 Read Left to Right to Branch**

WHAT IS PROPOSITON 65?



Proposition 65 requires businesses to provide warnings to Californians about significant exposures to chemicals that cause cancer, birth defects or other reproductive harm. These chemicals can be in the products that Californians purchase, in their homes or workplaces, or that are released into the environment. By requiring that this information be provided, Proposition 65 enables Californians to make informed decisions about their exposures to these chemicals.

Proposition 65 also prohibits California businesses from knowingly discharging significant amounts of listed chemicals into sources of drinking water.

Proposition 65 requires California to publish a list of chemicals known to cause cancer, birth defects or other reproductive harm. This list, which must be updated at least once a year, has grown to include approximately 900 chemicals since it was first published in 1987.

Why is Proposition 65 relevant to Robo-Fit Products?

Some products offered by Robo-Fit can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. Robo-Fit parts are to be used only for non-potable services, unless they have been given the "PBF" distinction on their corresponding part numbers.

By law, a warning must be given for listed chemicals unless the exposure is low enough to pose no significant risk of cancer or is significantly below levels observed to cause birth defects or other reproductive harm.

Businesses are required to provide a "clear and reasonable" warning before knowingly and intentionally exposing anyone to a listed chemical, unless the business can show that the anticipated exposure level will not pose a significant risk of cancer or is significantly below levels observed to cause birth defects or other reproductive harm.

This warning can be given in several ways, such as by labeling a consumer product, posting signs at the workplace, distributing notices at a rental housing complex, or publishing notices in a newspaper. The requirement to provide warnings takes effect one year after a chemical is added to the list.

Robo-Fit products will be labeled in the following manner in order to be compliant with Proposition 65:



WARNING: Products offered by Robo-Fit can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SAE STANDARDS



J246
Covers complete general and dimensional specifications for tube fittings of the spherical and flanged sleeve compression types for use in the piping of air brake systems on automotive vehicles.
J476
Covers Dryseal American Standard Taper Pipe Thread
J512
Covers complete general and dimensional specifications for the various types of tube fittings intended for general application in the automotive, appliance, and allied fields.
J513
Covers complete general and dimensional specifications for refrigeration tube fittings of the flare type.
J530
Covers complete general and dimensional specifications for those types of pipe fittings commonly used in the automotive and other mass production industries where the use of lubricants or sealers is objectionable.
J531
Covers complete general and dimensional specifications for those types of pipe, filler, and drain plugs commonly used in automotive and related industrial applications.
J844
Covers the minimum requirements for nonmetallic tubing as manufactured for use in air brake systems.
J1131
This SAE Standard is intended to establish uniform methods of testing SAE J844 tubing and fitting assemblies as used in automotive air brake systems.
J1615
This SAE Recommended Practice is intended as a guide to assist designers and/or users in the selection and application of various types of thread sealants.
J2494
Covers general and dimensional specifications for brass bodied reusable Push to Connect tube fittings for use in the piping of vehicular air brake systems.

*Reference listings to SAE products will meet functional requirements; construction may differ from specification.

For further detail consult SAE handbook or <http://www.sae.org/>



PIPE THREAD ASSEMBLY

Straight Fittings:

1. Hand Tighten
2. 1/8" to 1/2": Wrench Tight 2 Full 360° Turns
1/2" & Above: 1 1/2" Full Turns

Shaped Fittings:

1. Hand Tighten
2. Wrench Tight 1" to 1 1/2" Full 360° Turns

**For NPTF Pipe Threads with Pre-Applied Sealant*



PUSH-LOK FITTING ASSEMBLY

1. Make a clean square cut on your hose end.
2. Use lubricant on the end of the hose.
3. Move the fitting into the hose so only one barb is inserted into the hose. Make sure the fitting is lined up properly with the hose.
4. Push the fitting fully into the hose so that the end of the hose is covered by the yellow plastic cap. Make sure the fitting is fully inserted before use.



NYLON AIR BRAKE COMPRESSION END ASSEMBLY

1. Cut tubing squarely—using a tube cutter.
2. Make sure all fittings involved in the assembly are clean of burrs and debris.
3. Insert nylon air brake tubing firmly into the fitting until it bottoms out.
4. Tighten nut according to the chart listed below:

Tube Size	Turns Past Hand-Tight
3/16	2.5
1/4	3
3/8 + 1/2	4
5/8 + 3/4	3.5



DOT PUSH TO CONNECT NYLON AIR BRAKE COMPRESSION END ASSEMBLY

To Connect Fitting & Tubing:

1. Cut tubing squarely—using a tube cutter.
2. Make sure all fittings involved in the assembly are clean of burrs and debris.
3. Insert the nylon air brake tubing past the O-Ring until the tubing bottoms out against the tube stop.
4. Check your connection by pulling on the tubing to ensure tubing is fully inserted.




To Disconnect Fitting & Tubing:

1. Press and hold the collet against the fitting body.
2. Pull the tubing out of fitting.



AIR BRAKE HOSE END ASSEMBLY

1. Slide the nut/spring guard over the J1402 air brake hose.
2. Slide the sleeve over the hose, making sure the tapered edge of the sleeve is facing the fitting body (shown below).
3. Push the hose over the fitting body until the hose bottoms out.
4. Tighten the nut until there is contact with the fitting body's hex.



Working pressures and other technical information has been prepared from sources deemed to be reliable but no responsibility can be assumed by Robo-Fit, Inc. for the accuracy of this information under varied field conditions. It should be considered as a recommendation only and not a guarantee.

QUALITY CONTROL EQUIPMENT

One of Robo-Fit's goals is to supply our customers the highest quality product available. In pursuit of that goal, we have invested in an Image Dimension Measurement System, the "New Standard" for the Manufacturing Industry.

FAST

- No time consuming positioning work or datum setup required
- Measure up to 99 dimensions on up to 100 parts with the push of a button
- Automatically saves measurement data and creates inspection reports

CONSISTENT

- Automatically identifies measurement points, ensuring that the same measurement results are obtained each time
- Automatic focal adjustment prevents inconsistent values
- The simple place-and-press operation means consistent measurement results regardless of the operator

EASY

- Easily set up measurements with just a few clicks
- Setting up virtual lines and points is just as simple
- Automatically saves measurement data and creates inspection reports



DO YOU KNOW WHAT'S IN YOUR BRASS?

Knowing the material composition of your brass products is important. Most brass suppliers use material certificates from the brass mills to certify the chemical composition of their products. At Robo-Fit, we assume the mantra of "trust but verify."

X-ray fluorescence involves sophisticated physics, this process can be summarized as (i) X-rays out, (ii) X-rays back, (iii) fancy math, (iv) answer. The instrument can be used to determine the composition of nearly any type of sample.



Handheld XRF Analyzer





ROBO-FIT, LLC

2275 EAST ENTERPRISE PKWY, TWINSBURG, OH 44087

PHONE (440) 893-9878 • FAX (440) 893-9876

WWW.ROBO-FIT.COM



*"Making Connections Like Family,
Because That's Who We Are"*