

SPRING BOTTOM VALVES

CONSTRUCTION

- CA360 Brass
- CA377 Brass



APPLICATIONS

- In Line Shut-Off
- Air Lines
- Water Lines
- Drain Valves

RANGES

- Maximum Pressure :
30 PSIG
- Maximum Pressure:
H Series 150 PSI
- Temperature: -20° F to +250° F




FEATURES/BENEFITS

- Forged Brass Body
- Plug Style Valve
- Economic Tight Shut Off
- Made in USA



NOTES


- Parts that include “PBF” are supplied as low lead compliant.
- Part numbers without the “PBF” distinction are NOT lead free complaint.
- Non-stock items and special parts are available on a quotation basis.
- Configurations and dimensions are subject to change without notice.



MADE IN USA

130C FPT x MPT SPRING BOTTOM VALVE

PART NUMBER	FPT	MPT
130C-J	1/8"	1/8"
130C-L	1/4"	1/4"
130C-N	3/8"	3/8"




134C COMPRESSION SPRING BOTTOM VALVE

PART NUMBER	O.D. TUBE	O.D. TUBE
134C-4	1/4"	1/4"
134C-5	5/16"	5/16"
134C-6	3/8"	3/8"
134C-8	1/2"	1/2"




131C MPT x MPT SPRING BOTTOM VALVE

PART NUMBER	MPT	MPT
131C-J	1/8"	1/8"
131C-L	1/4"	1/4"
131C-N	3/8"	3/8"



135C FLARE x MPT SPRING BOTTOM VALVE

PART NUMBER	O.D. FLARE	MPT
135C-4J	1/4"	1/8"
135C-4L	1/4"	1/4"
135C-5J	5/16"	1/8"
135C-5L	5/16"	1/4"
135C-6L	3/8"	1/4"



132C FPT x FPT SPRING BOTTOM VALVE

PART NUMBER	FPT	FPT
132C-J	1/8"	1/8"
132C-L	1/4"	1/4"
132C-N	3/8"	3/8"



136C FLARE x MPT SPRING BOTTOM

PART NUMBER	O.D. FLARE	O.D. FLARE
136C-4	1/4"	1/4"
136C-5	5/16"	5/16"
136C-6	3/8"	3/8"
136C-8	1/2"	1/2"



133C TUBE x MPT SPRING BOTTOM VALVE

PART NUMBER	O.D. TUBE	MPT
133C-4J	1/4"	1/8"
133C-4L	1/4"	1/4"
133C-5J	5/16"	1/8"
133C-5L	5/16"	1/4"
133C-6L	3/8"	1/4"
133C-6N	3/8"	3/8"



138C FLARE x FPT SPRING BOTTOM

PART NUMBER	O.D. FLARE	FPT
138C-8P	1/2"	1/2"

